



# MULTIFAK<sup>®</sup> 2

---

Multifak 2 is a multipurpose lithium soap grease NLGI 2 with anti-wear, rust and oxidation additives.

## APPLICATION

Multifak 2<sup>1</sup> is especially indicated to lubricate electric motors and other industrial applications operating on high speed and low shock loads.

Multifak 2 can also be used as a multipurpose grease for industrial plain and roller bearings when an extreme pressure additive is not required. Multifak 2 has good water resistance, excellent shear stability and is formulated with low viscosity base oil (100 cSt at 40°C that is half of the base oil viscosity of conventional greases as Marfak MP 2 and Multifak EP 2).

## BENEFITS

Multifak 2 grease provides:

- **Good water resistance** — Provides lubrication in the presence of water.
- **Good corrosion protection** — Inhibited to protect metal surfaces.
- **Good oxidation stability** — Helps to ensure long life in storage and in use.
- **Good low temperature pumpability** — Better handling in the container and grease dispensing equipment.

## HANDLING PRACTICES:

For information on the safe handling and use of these products, refer to their Material Safety Data Sheet (MSDS).

---

1. Product manufactured in Brazil

## TYPICAL CHARACTERISTICS

	ASTM Method	
Product Code		1990
MSDS Code		
Soap		Lithium
Appearance		Amber
NLGI Grade	D-217	2
Worked Penetration, @ 25°C, 60 Strokes	D-217	274
Dropping Point, °C	D-2265	197
Base oil Viscosity		
cSt @ 40°C	D-445	98.7
cSt @ 100°C	D-445	10.7

Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing