



Lanka Super Plus

Passenger Car Motor Oil

Product Data Sheet

Customer benefits

Long engine life

Proven metallo-organic anti-wear additive system resists wear under all operating conditions by forming a protective layer on contact surfaces.

Preserves power and performance

Metallic detergent and ashless dispersant additive system preserves power and performance by providing good control of piston and ring deposits under high temperature conditions.

Saves on maintenance

Very good thermal and oxidation stability resists in-service oil degradation that contributes to filter blocking and sludge formation.

Applications

- Naturally aspirated and turbocharged gasoline engines in passenger cars where API SL or lower performance monograde oils are specified
- Light truck gasoline engines where API SL or lower performance monograde oils are specified
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils of API SL or lower performance

Not recommended for use in diesel engines or in motorcycle engines.

Product features:

- High quality monograde engine oil for use in a wide range of passenger car and light-duty commercial vehicle gasoline engines where API SL performance, monograde lubricants are required. It provides a high level of protection against heat stress and engine deposits.

Typical key properties

LANKA SUPER PLUS	TYPICAL RESULTS	
SAE Grade	30	40
Product Code	579114	579115
Base No., D2896, mg KOH/g	5.8	5.8
Phosphorus, m %	0.100	0.100
Sulfated Ash, m %	0.80	0.80
Viscosity		
mm ² /s @ 40°C	91.0	128
mm ² /s @ 100°C	11.5	14.3
Zinc, m %	0.11	0.11

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them. 2105

Performance standards

- API SL (licensed)

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltex.com.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Global Lubricants
– Asia Pacific