Product Data Sheet







Customer benefits

Engine Protection

Proven formula protects contact surfaces to control engine wear.

Smooth Riding

Effective and efficient technology that keeps engines clean by controlling engine deposits for sustained power release and acceleration.

Clean Engine

Stability at high temperatures combats oil degradation and prevents filter blocking and sludge formation.

Applications

- · Air and liquid-cooled, four-stroke motorcycle engines
- Motorcycles with oil-immersed clutches (where oils of this performance level are appropriate)
- · Motorcycles with centrifugal clutches
- · Four-stroke scooter engines

Product features:

• Havoline®Ezy 4T is a high quality, shear-stable, multigrade, multifunctional fluid specifically designed for use in four-stroke motorcycle engines, clutches and gearboxes, and portable power equipment engines requiring JASO MA, API SG lubricants.







Product specifications

HAVOLINE®EZY 4T KEY PROPERTIES	
SAE Grade	25W-40
Product Code	500700
Base No., D2896, mgKOH/g	7.0
Sulfated Ash, mass %	0.93
Viscosity, mm²/s @ 40°C mm²/s @ 100°C Viscosity Index Phosphorus, mass %	124 13.5 104 0.09

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.havoline.com.

1106

Performance standards

- JASO MA (2006)

 JASO Identification Number M061CTC344
- API SG

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:

Chevron Lubricants

Asia Pacific