

# Havoline<sup>®</sup> Super 2T

Low Smoke, Semi-Synthetic, Low-Stroke Motorcycle Oil



## Product description

Havoline<sup>®</sup> Super 2T is a premium two-stroke motorcycle oil, that helps protect vital engine parts while you ride.

## Customer benefits and product features

### Customer benefits

#### Powerful throttle response

Power and good acceleration are maintained by helping provide excellent cleanliness of pistons and exhaust ports, through the reduction of ash and carbon deposits.

#### Reduces exhaust smoke

Exceptional combustion characteristics help reduce smoke in exhaust emissions, which also helps provide improved working environment for operators of portable power equipment.

#### Helps extend engine life

Semi-synthetic base fluid provides excellent lubricity to help reduce wear of pistons and cylinders.

#### Helps maximise spark plug life

Low ash additive system helps reduce ash build-up on spark plugs under all standard operating conditions.

## Applications

- Air and liquid-cooled two-stroke motorcycle engines
- Particularly suitable for Japanese high performance motorcycle engines
- Japanese two-stroke engines fitted to portable power equipment (other than chainsaws)
- Oil-injected engines (except marine outboard) where no fuel/oil premixing is required
- Air-cooled, oil-gasoline premix engines at manufacturers' recommended gasoline-to-oil ratios, up to 50:1
- Two-stroke motorcycle and motor tricycle engines fitted with exhaust catalysts

*Not recommended for use in marine outboard engines, in chainsaw or in CNG- or LPG-fuelled engines.*

## Product approvals, performance, and recommendations

### Performance standards

Developed independently by Chevron to comply with:

- JASO FC  
JASO Identification Numbers: 065CVX686, 065CVX687
- ISO EGC
- API TC

# Havoline<sup>®</sup> Super 2T

Low Smoke, Semi-Synthetic, Low-Stroke Motorcycle Oil



## Typical Test Data

HAVOLINE <sup>®</sup> SUPER 2T KEY PROPERTIES	RESULT
<b>SAE Grade (J1536)</b>	<b>F/M 2</b>
<b>Product Code</b>	<b>500676</b>
Flash Point, PMCC, °C	93
Pour Point, °C	-38
Sulfated Ash, m %	0.13
Viscosity,	
mm <sup>2</sup> /s @ 40°C	59.2
mm <sup>2</sup> /s @ 100°C	9.4

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

HVLNESP2T/AP/PDSv2\_14/05/2019



**A Chevron company product**

© 2023 Chevron Products Company. Asia-Pacific.  
All Rights Reserved.