Super Tractor Oil Universal



Product description

Super Tractor is a shear stable, multi-viscosity super tractor oil universal (STOU) fluid designed for use in tractor engines, transmissions, final drives and hydraulic systems.

Customer benefits

Customer benefits

Minimizes application problems

Unique multi-application additive package enables use in engines, transmissions, final drives and hydraulic systems, avoiding costly equipment failure due to misapplication.

Reduced maintenance costs

Outstanding oxidation and nitration resistance minimizes acid number increase, providing protection against bearing corrosion.

Extended oil change periods

Very high oxidation stability protects against the formation of gums and varnishes, reduces oil thickening and increases oil life.

Maintains power output

Detergent/dispersant additive system maintains power output by providing deposit control under the high temperature conditions encountered in both naturally aspirated and turbocharged diesel vehicles. Multiviscosity characteristics ensure rapid oil circulation on start-up, preventing wear which contributes to power loss.

Smooth and quiet operation

Special friction modifier component allows smooth action of the wet brakes and power take-off clutches, minimizing chatter, stick slip and squawk.

Super Tractor Oil Universal



Applications

- Where tractor manufacturers specify the use of a STOU type product.
- Mixed fleets of agricultural tractors and associated equipment.
- Enclosed oil immersed (wet) brakes.
- Power take off (PTO) clutches.

Approvals, performance and recommendations

Performance standards

- API CF, CF-4/SF
- API GL-4
- ZF TE-ML 06B, TE-ML 07B (approved and listed, reference 000789)

Suitable for use where the following are specified:

- API CG-4
- ACEA E3-96
- Ford ESN-M2C159-B
- Ford New Holland FNH 89008903
- New Holland NH 024C
- Massey Ferguson CMS M-1144, M-1145

Super Tractor Oil Universal



Service considerations

Super Tractor SAE 15W-40 is a multifunctional fluid of the super tractor oil universal (STOU) type that is intended for use in both the engines and transmission compartments of agricultural tractors and related equipment, including those fitted with oil-immersed brakes.

For current and recent tractors, manufacturers separately specify the engine oil and transmission fluid requirements. Thus in each case it is necessary to determine that Super Tractor SAE 15W-40 meets both sets of requirements. Historically some tractor makers issued a single STOU specification that covered both engines and transmission, but this practice has been discontinued for many years.

The diversity of tractor transmission fluid specifications is such that there are some mutual exclusivities, and it is not possible for one fluid to completely meet all specifications. Also, some specifications are not publicly available. Thus in some cases, Super Tractor SAE 15W-40 is offered on a suitable-for-use basis, supported by a comprehensive combination of bench and equipment testing.

Although Super Tractor SAE 15W-40 does meet API GL-4, this is a secondary target and it is nevertheless not designed for nor intended for use in any on-highway drive axles of the hypoid type.

Super Tractor Oil Universal



Typical test data

SUPER TRACTOR	
SAE Grade	15W-40
Product Code	500421
Base No., D2896, mg KOH/g	10.1
Pour Point, °C	-33
Sulfated Ash, m %	1.4
Viscosity, Kinematic mm²/s @ 40°C mm²/s @ 100°C	113 15.1
Viscosity Index	139
Zinc, m %	0.14

Minor variations in product typical test data are to be expected in normal manufacturing

2206

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.



and Pakistan. All Rights Reserved.