

Havoline® Formula SAE 15W-40 & 20W-50

Passenger Car Motor Oil



Product description

Highly shear-stable, multigrade gasoline engine oil formulated from selected base fluids for use in passenger car and light truck engines requiring API SL or lower performance lubricants and where SAE 15W-40 or 20W-50 viscosity grading is acceptable.

Customer benefits and product features

Customer benefits

- **Long engine life**
Proven metallo-organic anti-wear additive system protects engines under all operating conditions by providing excellent wear control. Multigrade viscosity provides additional protection against wear under high temperature operating conditions.
- **Maintains high power and performance**
Metallic detergent and ashless dispersant additive system maintains high power and performance by providing excellent control of piston and ring deposits under high temperature conditions.
- **Saves on maintenance costs**
High thermal stability and oxidation resistance provides excellent protection against in-service oil degradation that contributes to filter blocking and sludge formation in the oil galleries, crankcase and valve train.
- **Low oil consumption**
Highly shear-stable viscosity index improver controls oil flow through the piston rings by maintaining high-temperature oil viscosity within the ring belt area in all services.

Applications

- Naturally aspirated gasoline engines in passenger cars and light commercial vehicles.
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

Not recommended for use in engines that require ILSAC or ACEA-classified oils, in turbocharged engines, in CNG or LPG-fuelled engines, in any diesel engines or in motorcycle engines.

Product approvals, performance and recommendations

Performance

- API SL (licensed)
- API CF

Havoline® Formula SAE 15W-40 & 20W-50

Passenger Car Motor Oil



Typical test data

HAVOLINE® FORMULA	RESULTS	
SAE Grade	15W-40	20W-50
Product Code	500736	500259
Base No., D2896, mg KOH/g	5.9	5.9
Phosphorus, m %	0.11	0.11
Sulfated Ash, m %	0.95	0.95
Viscosity, mm ² /s @ 40°C mm ² /s @ 100°C	113 15	153.2 17.7
Viscosity Index	134	127
Zinc, m %	0.12	0.12

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Havoline® Formula SAE 15W-40 and 20W-50/MEA/CHV/PDSv1_03/2024



Chevron company product

© 2024 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.