

Sports Utility Vehicle Engine Oil



Product description

Delo® Sports Synthetic Blend SAE 10W-30 is a high performance, multigrade, diesel engine oil specifically designed to meet the requirements of sports utility, sports activity, pick-up and 4x4 type vehicles, especially the latest models with common-rail fuel injection system-equipped engines, where heavy duty type motor oils (HDMOs) are preferred.

Customer benefits and product features

Customer benefits

- Prolongs engine life Very high oxidation stability combined with excellent dispersancy and anti-wear
 characteristics minimize deposit formation and wear, extending engine life. Control of soot related wear is
 especially important in SUV type diesel engines subject to stop/ start city driving or in hard working off-road
 service. Multigrade viscosity provides additional protection against wear at start-up and under high
 temperature operating conditions. Provides 61% more protection to camshaft against wear* and 28% better
 control on piston deposits**.
- Preserves full power and performance High performance combination of synthetic blend base fluid and outstanding metallic detergent additive system preserves full power and performance by providing excellent upper-ring-belt deposit control under the high temperatures encountered in turbocharged diesel engines.
- **Reduces operating costs** Exceptional wear control demonstrated in the Japanese JASO DH-1 wear tests translates into improved engine durability and reduced maintenance costs.
- Reduces oil consumption Synthetic blend base fluid and highly shear-stable viscosity index improvers
 provide superior control of oil flow through the ring belt area by maintaining oil viscosity, and reduce oil
 evaporation at the elevated ring zone temperatures experienced under high temperature on or off-road
 conditions.
- Preserves fuel efficiency Optimized and highly stable viscosity characteristics ensure preservation of fuel economy in modern engines that are designed to take full advantage of lower viscosity oils. Provides up to 1.3% fuel economy savings***.

Product features

- Delo® Sports Synthetic Blend SAE 10W-30 is suitable where performance requirements up to and including API CI-4 are called for.
- Delo® Sports Synthetic Blend SAE 10W-30 is formulated from high performance hydrocracked base oils combined with selected synthetic base fluids.

^{*}Test result according to JASO DH-1 passing limit for average camshaft parameter using the Mitsubishi 4D34T4 engine test

^{**}Test result according to API CI-4 passing limit for average weighted piston deposits using the Seq IIIF (ASTM D6984) engine test

^{***} Test results according to fuel economy savings versus using an SAE 15W-40 API CI-4 HDMO equivalent product



Sports Utility Vehicle Engine Oil

Applications

- Light-duty diesel engines fitted with common rail fuel injection systems where HDMO type oils of API CI-4 or lower performance are required.
- Diesel-engined sports utility and sports activity recreational vehicles where HDMO type oils of API CI-4 or lower performance are required.
- Diesel-engined high performance pick-up and 4x4 type vehicles where HDMO type oils of API CI-4 or lower performance are required.
- Other diesel powered passenger car and light commercial vehicles where HDMO type oils of API CI-4 or lower performance are required.
- Diesel engines utilizing diesel fuels with up to 20% biodiesel (B20)*

Product approvals, performance and recommendations

Performance

- API CI-4 (licensed)
- JASO DH-1 (JASO ID: D065CTP888)



Sports Utility Vehicle Engine Oil

Service considerations

Light-duty diesel engines, as used in passenger cars, light commercial vehicles and sport-utility vehicles vary in their lubricant requirements. Typically the requirement is for engine oils that have been designed expressly for lightduty diesel engines, and which meet one of the major light-duty diesel engine oil specifications, such as ACEA A3/B4, the ACEA C-series Sequences, and JASO DL-1. These specifications require performance characteristics that are somewhat different to those customarily associated with heavy-duty engine oils (HDMOs). For such engines, an appropriate oil selection may be made from the Havoline® Fully Synthetic and Havoline® Synthetic Blend range of products.

Nevertheless there are some light-duty diesel engines, particularly those from Asian builders, for which HDMOs that meet a current or recent API C-series category are either required or acceptable. The Delo[®] Sports series is intended for use in such engines.

When using with biodiesel blends containing >6% B100, monitoring oil condition is critical. Fuels with higher biodiesel content increase the risk of fuel dilution in the engine oil. This reduces the oxidation stability of the engine oil as biodiesel tends to oxidise more rapidly thus directly impacting the oil drain intervals. Biodiesel contents greater than B5 have a lower energy content than diesel fuel, which may result in slight horsepower loss and slightly increased fuel consumption.

Always follow OEM recommendation for appropriate fuel and engine oil selection.



Sports Utility Vehicle Engine Oil

Typical test data

DELO® SPORTS SYNTHETIC BLEND SAE 10W-30	RESULTS
SAE Grade	10W-30
Product Code	500579
Base No.,	
D2896, mg KOH/g	10.4
D4739, mg KOH/g	10.0
Phosphorus, m%	0.13
Sulfated Ash, m %	1.5
Viscosity, mm²/s @ 40°C mm²/s @ 100°C	82.3 12.2
Viscosity Index	144
Zinc, m%	0.15

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Asia-Pacific region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.