



# Texclad<sup>®</sup> AL EP 0

## High performance sprayable aluminium complex grease lubrication

### Product description

Texclad AL EP 0 is a high performance sprayable aluminium complex grease. It is formulated with a quality mineral base oil in combination with a very fine graphite component.

### Customer benefits

- High stability sprayable aluminium complex formulation
- Reliable oxidation stability helps resist breakdown
- Robust, high pressure load capacity assists in wear protection
- Effective adhesion and water resistant properties
- Formulation contributes to corrosion resistance
- High thermal load capacity

### Applications

- Texclad AL EP 0 is designed for automatic spray lubrication of toothed wheels, gear rings, toothed racks and pinions, operating under high pressure and temperatures. It is suitable for the lubrication of rotary furnaces or similar hot lubricating points even under dusty and wet conditions
- Texclad AL EP 0 is pumpable and suited for applications in centralised lubricating systems employed increasingly in the mining, sugar, cement and steel industries. With a wide operating temperature range from  $-20^{\circ}\text{C}$  to  $+200^{\circ}\text{C}$ , Texclad AL EP 0 offers smooth machine and aggregate operation
- Attention must be paid to ensure that under scheduled lubrication a maximum temperature of  $+200^{\circ}\text{C}$  is not exceeded. At temperatures in excess of this, continuous re-lubrication must be ensured or shorter re-greasing intervals introduced, subject to thermal load. Under these conditions temperatures up to  $+250^{\circ}\text{C}$  may be reached

### Product highlights

- **Highly stable and sprayable**
- **Reliable oxidation and thermal stability**
- **High pressure load capacity**
- **Adhesive and water resistant**
- **Helps resist corrosion**

#### Selected specification standards include:

DIN

ISO

## Approvals, performance and recommendations

### Performance

	DIN 51 502	ISO 6743-09	Operating temperature
Texclad AL EP 0	OGPF 0S-20	ISO-L-XBGHB0	-20 °C up to +200 °C, with short periods up to +250 °C

Typical test data		
Test	Test methods	Results
Viscosity Grade	DIN 51 818	0
Product Code		27115
Appearance	-	Black, smooth
Thickener type	-	Aluminium complex
Penetration worked, 60x, mm/10	DIN ISO 2137	355-385
Dropping Point, °C	DIN ISO 2176	> 250
Graphite content, %	-	10
Base oil type	-	Semi-synthetic
Base oil viscosity at 40°C, mm <sup>2</sup> /s	DIN 51 562	500
Emcor corrosion test	DIN 51 802	1/1
Copper Corrosion 24hrs at 100°C	DIN 51 811	1B
Four Ball weld point, N	DIN 51 350	7000
Water resistance static	DIN 51 807/1	0-90

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

**Disclaimer** Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheets.

**Health, safety, storage and environmental** Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

### A Chevron company product