

Havoline® Power 2T

Two-Stroke Motorcycle Oil



Product description

Havoline® Power 2T is a cost-effective “low smoke”, semi-synthetic two-stroke motorcycle oil formulated with a low ash additive system. Prediluted with a high flash point, low odor solvent to facilitate mixing with gasoline at all temperatures. Designed for engines requiring JASO FC performance lubricants.

Customer benefits and product features

Customer benefits

- **Reduces exhaust smoke**
Superior combustion characteristics of the special blend of synthetic component and highly refined mineral oil significantly reduce visible smoke in exhaust emissions.
- **Longer spark plug life**
Low ash additive system reduces spark plug fouling under all operating conditions.

Applications

- Air and liquid-cooled two-stroke motorcycle engines
- Motorcycle engines that require JASO FC performance oils.
- Two-stroke scooter engines
- Oil-injected engines (except marine outboard) where no fuel/oil premixing is required
- Air-cooled, oil-gasoline premix engines at manufacturers’ recommended gasoline-to-oil ratios, up to 50:1
- Two-stroke motorcycle and motor tricycle engines fitted with exhaust catalysts

Not recommended for use in any marine outboard engines.

Not recommended for use in any CNG- or LPG-fuelled two-stroke engines.

Approvals, performances and recommendations

Performance standards

- JASO FC (Jaso Identification Number: 065CVX664)
- ISO EGC
- TIS 1040-2541

Havoline® Plus 2T

Two-Stroke Motorcycle Oil



Typical test data

HAVOLINE® POWER 2T

SAE Grade (J1536)	F/M 2
Product Code	500708
Flash Point, PMCC, °C	98
Pour Point, °C	-15
Sulfated Ash, m %	0.08
Viscosity,	
mm ² /s @ 40°C	57.3
mm ² /s @ 100°C	8.79

2106

Service considerations

Havoline Power 2T is not recommended for use in marine outboard engines, chainsaw engines unless the OEM recommends the performance levels which this product meets, or any CNG- or LPG-fuelled two-stroke engines.

Havoline Power 2T is not recommended for use in any applications where API TC performance oils are required.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Havoline® Power 2T/Asia Pacific/CHV/PDSv1_04/2024



A Chevron company product

© 2024 Chevron Products Company. Asia Pacific.
All Rights Reserved.