



# CHEVRON MINING HYDRAULIC OILS AW

## ISO 68, 100

---

### PRODUCT DESCRIPTION

Chevron Mining Hydraulic Oils AW are used in non-critical, once-through applications in mining equipment.

### CUSTOMER BENEFITS

Chevron Mining Hydraulic Oils AW deliver value through:

- **Controlled costs** — a low cost economical product for non-critical applications.

### FEATURES

Chevron Mining Hydraulic Oils AW are low cost hydraulic oils containing line wash flush oils.

### APPLICATIONS

Chevron Mining Hydraulic Oils AW are typically used for once-through applications in older hydraulic mining equipment.

Appearance, color, odor, and water content may vary depending on the content and source of flush oils used.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

### TYPICAL TEST DATA

ISO Grade	68	100
Product Number	229007	229008
MSDS Number	6791	6791
API Gravity	29.4	30.5
Viscosity, Kinematic cSt at 40°C	71.1	100
Flash Point, °C(°F)	180(356)	180(356)
Copper Corrosion D130	≤ 4a	≤ 4a
Water Content, ppm	< 2000	< 2000

Minor variations in product typical test data are to be expected in normal manufacturing.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

25 February 2010  
IO-905

©2004-2010 Chevron Products Company, San Ramon, CA. All rights reserved.

Chevron and the Chevron Hallmark are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.