

Gear Oil ZF

“Limited Slip” Automotive Gear Oil



Product description

High performance, EP automotive gear oil specifically designed for “limited slip” rear drive differentials, particularly those of ZF design with multiplate clutches. Its special friction properties help to provide smooth, noise free operation of and extended life of these units.

Customer benefits

- **Quiet, shudder-free operation**
Special friction modifier system provides excellent lubricity characteristics for smooth, non-stick/slip engagement and disengagement of limited slip differential plate clutches.
- **Long gear life**
Effective EP additives control gear tooth wear, even under high torque, low speed and shock loading conditions. Rust and corrosion inhibitors prevent component damage by water of condensation or contamination.

Applications

- ZF limited slip differentials, including those with hypoid gears, as fitted to cars, trucks and buses and off-highway equipment.
- Other limited-slip differentials where oils meeting ZF TE-ML 05C, and 21C are specified.

Note: Appearance of product can turn hazy at temperatures below 5°C. This is due to the presence of friction modifier additives needed in limited slip differential mechanisms. Hazy appearance will not affect lubricant performance.

Approvals, performance and recommendations

- API GL-5 (self-certified)
- ZF (approved):
 - TE-ML 05C
 - TE-ML 21C
- John Deere JDM J11F (self-certified)

Gear Oil ZF

“Limited Slip” Automotive Gear Oil



Typical test data

GEAR OIL ZF

| | |
|----------------------------|---------------|
| SAE Grade | 80W-90 |
| Product Code | 510310 |
| Pour Point, °C | -30 |
| Oil Viscosity, | |
| mm ² /s @ 40°C | 147 |
| mm ² /s @ 100°C | 15.0 |
| Viscosity Index | 102 |

Minor variations in product typical test data are to be expected in normal manufacturing.

2207

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

Gear Oil ZF/MEA/CHV/PDSv1_06/2024



Chevron company product

© 2024 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.