



Texaco Synthetic ATF Heavy Duty

Synthetic Automatic Transmission Fluid

Product Data Sheet

Customer benefits

- **Extended oil life**
Synthetic base fluid and inhibitor package provide outstanding oxidation resistance and thermal stability which prevents acid buildup, oil thickening and deposit formation and can extend oil drain interval up to four times that of conventional ATF.
- **Smooth operation**
Combination of synthetic base fluid, special viscosity index improver and advanced friction modifiers provides excellent lubricating qualities at high and low temperatures and smooth shifting and efficient power transfer under all service conditions.
- **Maximizes transmission life**
Highly stable viscosity index improver resists break down under high shear conditions found in modern transmissions, maintaining oil viscosity and film thickness to protect moving components. Superior antiwear properties and resistance to sludge formation extend the time to transmission overhaul in severe service conditions.
- **Minimizes inventory**
Effective EP additive, viscosity characteristics and a wide range of manufacturers' approvals allows use in a variety of automotive, industrial and marine applications, reducing risk of misapplication.

Applications

- On-highway heavy-duty automatic transmissions
- Off-highway heavy-duty automatic transmissions
- Car and light truck automatic transmissions
- Power steering units (where the manufacturer recommends DEXRON®-III or MERCON® fluid)
- Rotary vane and screw type air compressors (where this type of fluid is appropriate)


Product features:

Premium performance, multipurpose anti-wear automatic transmission fluid (ATF) formulated in ultra high viscosity index base fluid, with Allison Transmission, Mercedes Benz and Voith Turbo approvals. Specially designed for heavy duty automatic truck and bus transmissions operating in severe service.

A **Chevron** company product

All trademarks are property owned by Chevron Intellectual Property LLC.



- 
- Mobile hydraulic systems
 - Industrial anti-wear hydraulic systems
 - Marine anti-wear hydraulic systems
 - Manual transmissions and transaxles (where this type of fluid is appropriate)

Performance standards

Approvals:

- Allison Transmission TES-389 (AA-31992007)
- Allison Transmission C4 fluid (C4-31662005)
- MAN 339 Type V1 and Z2
- Mercedes Benz Sheet 236.9
- Voith Turbo H55.6335 (G607 List)
- Voith Turbo H55.6336 (Extended Drain approved)
- Volvo 97341
- ZF TE-ML 14B

Suitable for use where the following fluid specifications are recommended:

- Allison TES-295
- GM DEXRON®-III (obsolete)
- Ford MERCON® (obsolete)



Texaco Synthetic ATF Heavy Duty

Synthetic Automatic Transmission Fluid

continued

Product specifications

TEXACO SYNTHETIC ATF HEAVY DUTY KEY PROPERTIES	RESULTS
Product Code	510116
Color	Red
Pour Point, °C	-45
Viscosity, Brookfield mPa.s @ -40°C	11400
Viscosity, Kinematic mm ² /s @ 40°C	35.3
mm ² /s @ 100°C	7.4
Viscosity Index	183

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com