

HDAX[®] 5100 Ashless Gas Engine Oil

SAE 15W-40, 30, 40



Product description

HDAX[®] 5100 Ashless Gas Engine Oils are advanced performance, premium quality, ashless, natural gas engine oils.

Customer benefits

Customer benefits

- **Excellent low temperature performance**
HDAX 5100 Ashless Gas Engine Oil SAE 15W-40 is less viscous than SAE 30 and 40 oils at low temperatures, so it provides easy startup and improved cold temperature lubrication as compared to straight grades.
- **Promotes low maintenance cost and long engine life**
- **Minimizes ash deposits**
Protects against spark plug fouling from lubricating oil ash deposits. Minimizes ash deposits on valves, piston heads, combustion chamber surfaces, spark plugs, and port surfaces, minimizing the risk of pre-ignition and detonation.
- **Low ring and cylinder liner wear**
- **Exceptional engine cleanliness**
Minimizes engine deposits at both high and low operating temperatures through the use of an ashless dispersant.
- **Minimum viscosity increase in severe service**
Ashless oxidation inhibitor minimizes viscosity increase allowing for long oil drain intervals.
- **Proven performance** in older four-stroke naturally aspirated and turbocharged engines.

Product features

- HDAX 5100 Ashless Gas Engine Oils are formulated with Group II base stocks and a carefully balanced ashless package of dispersant, antioxidant, extreme pressure, and corrosion inhibitor additives.
- HDAX 5100 Ashless Gas Engine Oils are formulated without bright stock for all two-stroke and selected four-stroke high speed, high output, turbocharged natural gas engines operating at full capacity.
- HDAX 5100 Ashless Gas Engine Oils help provide exceptionally clean engine parts, even under severe operating conditions and extended overhaul intervals. They help protect against the formation of crankcase sludge and help to maintain clean exhaust ports in two-stroke engines.

HDAX[®] 5100 Ashless Gas Engine Oil

SAE 15W-40, 30, 40



Applications

HDAX 5100 Ashless Gas Engine Oils are recommended for all two-stroke and selected four-stroke stationary engines that require an ashless-type engine oil and which use natural gas.

They are the recommended lubricant for two-stroke gas engines with high compression ratios and turbochargers, and two-stroke engines known to be sensitive to combustion chamber and port deposits.

Product approvals, performance and recommendations

HDAX 5100 Ashless Gas Engine Oils are recommended for gas fueled engines manufactured by:

- Ajax
- Caterpillar (except 3400, 3500, 3600)
- Clark-Dresser
- Cooper Bessemer (two-stroke)
- Dresser-Rand (Ingersoll-Rand) Categories I and II
- Fairbanks-Morse/MEP
- Waukesha VR and Intermediate/Clinton
- Worthington (two-stroke)

SAE 15W-40 oils may not be appropriate for large medium speed gas engines.

Consult Chevron at lubetek@chevron.com before using HDAX 5100 Ashless Gas Engine Oil SAE 15W-40 in these applications.

HDAX® 5100 Ashless Gas Engine Oil

SAE 15W-40, 30, 40



Typical Test Data

HDAX® 5100 ASHLESS GAS ENGINE OIL	RESULTS		
SAE Grade	15W-40	30	40
Product Code	232308	232373	232307
SDS Number	26850	23850	7050
Density at 15°C, kg/L	0.8746	0.8773	0.8790
Viscosity, Kinematic			
cSt @ 40°C	128.6	95.6	120
cSt @ 100°C	15.72	11.6	13.7
Viscosity Index	128	109	111
Flash Point, °C(°F)	230(446)	252(486)	260(500)
Pour Point, °C(°F)	-34(-29)	-32(-26)	-26(-15)
Sulfated Ash, wt %	nil	nil	nil
Acid Number, ASTM D664	0.9	0.8	0.8
Base Number, ASTM D2896	2.8	2.8	2.8
Phosphorus, ppm	670	670	670
Zinc, ppm	<10	<10	<10

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.