



# Texaco Motor Oil S 5W-40

Effective performance multigrade engine oil

## Product description

Texaco Motor Oil S 5W-40 is an effective performance shear stable diesel and gasoline passenger car multigrade engine oil, designed to offer durable long-life wear resistance and engine cleanliness, with reliable cold-start protection.

Texaco Motor Oil S 5W-40 is formulated with quality base oils in combination with a robust additive package, offering good long-term engine performance and protection.

## Customer benefits

- Effective detergency promotes protection against varnish and sludge formation, ring sticking and offers improved engine performance
- Low ash forming additive content helps reduce deposit build-up in diesel particulate filters
- Low phosphorus and sulphur promotes increased lifetime to three-way catalytic convertors and other after treatment devices

## Product highlights

- **Promotes effective keep-clean engine performance**
- **Helps reduce deposits in diesel particulate filters**
- **Promotes increased lifetime to three-way catalytic convertors and other after treatment devices**

### Selected specification standards include:

ACEA

API

## Applications

- Texaco Motor Oil S 5W-40 is intended for use in gasoline engines and passenger car and light van diesel engines
- Texaco Motor Oil S 5W-40 is suitable for use in engines that require ACEA C3, API SN, API SM and the older API gasoline specifications such as API SL, API SJ, API SH and API SG

## Approvals, performance and recommendations

### Recommendations

- ACEA C3
- API SN

Typical test data		
Test	Test Methods	Results
<b>Viscosity Grade</b>		<b>5W-40</b>
Density at 15°C, kg/l	ASTM D4052	0.850
Viscosity, Kinematic at 40 °C, mm <sup>2</sup> /s	ASTM D445	76.0
Viscosity, Kinematic at 100 °C, mm <sup>2</sup> /s	ASTM D445	12.9
Viscosity Index	ASTM D2270	171
Pour Point, °C	ASTM D5950	-43
Flash Point COC, °C	ASTM D92	232

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

**Disclaimer** Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

**Health, safety, storage and environmental** Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

**A Chevron company product**