


# GM Synthetic Gear Oil SAE 75W-90

# Extreme Pressure Automotive Synthetic Gear Oil

Product Data Sheet







## **Applications**

• Factory-fill of drive axles on General Motors vehicles where oil to GM specification 9986115 is required.

#### Performance standards

• General Motors Specification 9986115 (factory-fill approval)

#### **Product features:**

Synthetic extreme pressure gear lubricant meeting General Motors specification 9986115 for factory-fill of drive axles.







## **Product specifications**

GM SYNTHETIC GEAR OIL	
KEY PROPERTIES	RESULTS
SAE Grade	75W-90
Product Code	510233
Pour Point,	-48
Viscosity:	
mm²/s @ 40°C	95
mm <sup>2</sup> /s @ 100°C	14.5
Brookfield Viscosity, at -40°C, mm↓3/s	80 000
Viscosity Index	157

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

<u>Disclaimer</u> Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

<u>Health, safety, storage and environmental</u> Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

#### For more information, go to www.chevronlubricants.com