



Havoline Ultra SAE 0W-20

High performance synthetic engine oil

Product description

Havoline® Ultra SAE 0W-20 is a high-performance synthetic engine oil suitable for use in petrol engines and hybrids. It is specifically formulated to meet the latest ILSAC GF-5 specification and the latest Ford specification for hybrid vehicles.

Havoline Ultra SAE 0W-20 is formulated with premium synthetic base oils, and advanced additive technologies designed to deliver improved fuel economy, emissions system protection and robust, reliable gasoline engine performance.

Customer benefits

- Advanced cleaning additives offer oxidation control, wear protection, cleanliness and acid neutralisation helping extend engine life under severe driving conditions
- Formulated for dependable turbocharger protection
- Designed to provide enhanced fuel economy in vehicles where 0W-20 engine oils are recommended
- Low SAPS formulation helps protect three way catalysts (TWC) and minimise exhaust emissions
- Low temperature fluidity aids rapid lubricant circulation during cold start-ups, contributing to increased engine protection

Product highlights

- **Helps extend engine life under severe driving conditions**
- **Formulated for dependable turbocharger protection**
- **Designed to provide enhanced fuel economy**
- **Low SAPS helps protect TWCs**
- **Aids cold start-up engine protection**

Selected specification standards include:

API	Chrysler
Fiat	Ford
ILSAC	

Applications

- Havoline Ultra SAE 0W-20 is suitable for use in gasoline passenger cars, with or without turbochargers. It is not intended for use in passenger car diesel engines.
- Havoline Ultra SAE 0W-20 is suitable for use in hybrid vehicles requiring engine oils that meet API SN, ILSAC GF-5 or Ford WSS-M2C947-A.
- Havoline Ultra SAE 0W-20 is an especially designed low friction, low viscosity oil and covers ILSAC GF-5 typically used for Honda, Mazda and other Japanese OEMs
- Havoline Ultra SAE 0W-20 can be used in combination with gasoline containing up to 85% ethanol (E85)

Havoline Ultra SAE 0W-20 is unsuitable for some engines. Consult owners' manual or handbook if in doubt

Approvals, performance and recommendations

Performance

- ILSAC GF-5
- API SN
- Ford WSS-M2C947-A

Recommendations

Suitable for use in

- Applications requiring Chrysler MS-6395
- Applications requiring Fiat 9.55525-CR1
- Applications requiring Fiat 9.55535-GSX

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 0W-20
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.850
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	46
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	8.25
Viscosity Index	ASTM D2270	155
Pour Point, °C	ASTM D5950	-39
Flash Point COC, °C	ASTM D92	232

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A Chevron company product