



Marfak® Multipurpose EP

Automotive and Industrial Grease

Product Data Sheet

Customer benefits

Protects equipment

Resistance to water washout retains grease in place in wet environments. Mechanical stability minimizes shear down of the grease, reducing leakage from bearings.

Good service life

Effective oxidation inhibitor reduces the degradation of the base oil in service, to enhance the service life of the grease.

Applications

Can include:

- General purpose automotive applications
- Industrial ball and roller bearings

Usable temperature range in continuous service is:

-30 to 125°C (NLGI 2)

-20 to 125°C (NLGI 3)

Product features:

- **Marfak® Multipurpose EP** is a general purpose grease containing an ISO 220 mineral base oil, a lithium thickener and oxidation inhibitor for use in general purpose automotive applications and industrial ball and roller bearings.

Typical key properties

MARFAK®MULTIPURPOSE EP		
NLGI Grade	2	3
Product Code	510853	510854
Dropping Point, °C	195	205
Oil Viscosity,		
- mm ² /s @ 40°C	200	200
- mm ² /s @ 100°C	17.6	17.6
Penetration, Worked @ 25°C	280	235
Thickener (Lithium), m %	7	9.5
Four-Ball Wear, mm	0.5	0.5

1403

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.chevronlubricants.com.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific