



Ursa Heavy Duty

SAE 15W-40 and SAE 20W-50

Heavy-duty multigrade engine oils

Product description

Ursa® Heavy Duty multigrade engine oils are designed to conform to ACEA, API and original equipment manufacturers performance standards for heavy duty diesel engines.

Ursa Heavy Duty multigrade engine oils are formulated with premium quality base oils and selected additive technologies to help provide good durable service and performance.

Customer benefits

- Designed for reduced low temperature sludge and protection against high temperature oxidation and piston deposit formation
- Formulated for detergency performance and acid control to help maintain reliability, preventing engine and bearing corrosion
- Promotes engine service life by helping protect against wear and bore polishing

Product highlights

- **Designed for sludge and oxidation resistance**
- **Formulated to help engine corrosion protection**
- **Promotes engine service life**

Selected specification standards include:

ACEA	API
Cummins	Deutz
Daimler Trucks	MAN
MTU	Volvo

Applications

Ursa Heavy Duty multigrades are developed for use in heavy duty engine operations, in both on and off highway service. They are designed for turbocharged and naturally aspirated diesel engines in various types of service, including engines used in heavy-duty trucks, construction, mining and farming equipment.

Ursa Heavy Duty SAE 15W-40 can also be used in mixed fleet (gasoline and diesel) engines.

Ursa Heavy Duty SAE 15W-40 and 20W-50 also provide protection in engines where oils are recommended meeting the former CCMC D4, PD2 and G4.

Approvals, performance and suitable for use

Approvals

- Deutz DQC II-18
- Daimler Trucks DTFR 15B110 (previously known as MB 228.3)
- MTU Oil Category 2 (for SAE 15W-40, approval request submitted)

Performance

- API CI-4, CH-4, CG-4, CF-4, SL
- ACEA E2-96 issue 5 A3/B3
- Cummins CES 20076
- MAN M3275-1*

Suitable for use

- API CE, CD, CF
- Mercedes Benz MB 229.1
- Volvo VDS

* Approvals obtained can be no longer extended since obsolete by MAN

Typical test data			
Test	Test Methods	Results	
Viscosity Grade		SAE 15W-40	SAE 20W-50
Shelf Life: 60 months from date of filling indicated on the product label			
Density at 15°C, kg/l	ASTM D4052	0.870	0.879
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	111	169
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	14.4	18.6
Viscosity Index	ASTM D2270	132	123
Pour point, °C	ASTM D5950	-42	-36
Flash point COC, °C	ASTM D92	235	252
Total Base Number, mg KOH/g	ASTM D2896	8.6	8.6
Sulphated Ash, %wt	ASTM D874	1.3	1.3

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A Chevron company product