



Talcor OGP-5

Product Description

TALCOR OGP-5 is an advanced lubricating compound blended with highly refined mineral and synthetic oils plus laminar micro solids and chemical additives.

Customer Benefits

Free of solvent, bitumen and heavy metals.
Can be dispensed without heating, through conventional spray lubricating systems.
High Four Ball Weld and FZG test results, thus providing excellent lubrication under boundary conditions.
Will not harden in the gear teeth roots and drains readily.
Advanced chemical and solid additives produce a durable lubricating film .

Applications

Heavy loaded Open Gears in grinding mills, kiln drives and slow moving bushes, bearings including certain type of enclosed gear cases as found in heavy industries (Mining, Cement, Sugar, Power Generation, etc)

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

Notes

Talcor OGP-5 is not recommended for use in HIGH SPEED journal or roller bearings.

Typical Properties

NLGI Grade	00	2
Product Code	571424	571586
Thickener	Mainly Synthetic	Mainly Synthetic
Base Fluid Viscosity @ 40°C (cSt)	1870	1870
Safe Operating Temperature °C	85	85
Four Ball Weld Point (kgf)	800	800
FZG Test, Stage Passed	12	12

The information in this bulletin is, to our best knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control. It is the user's obligation to evaluate and use the product safely and to comply with all applicable laws and regulations.

ENVIRONMENT, HEALTH and SAFETY Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.chevronlubricants.com.

