



DELO[®] ELI CORROSION INHIBITOR

PRODUCT DESCRIPTION

Delo[®] ELI Corrosion Inhibitor is a water-based inhibitor, super concentrate, using a patented synergistic combination of aliphatic carboxylates that also contains nitrite and molybdate as secondary inhibitors.

CUSTOMER BENEFITS

Delo ELI Corrosion Inhibitor delivers value through:

- **Long Service Life** — 600,000 miles, 1,000,000 km, 12,000 hours, 6 years in on-road and off-road engine applications and **32,000 hours** or 8 years in stationary engines with yearly testing required.
- **Corrosion Protection** — Extended life corrosion protection in aqueous solutions for engine metals, including aluminum, iron, steel, brass, copper and solder alloys.
- **Compatibility** — Compatible with glycol-based engine coolants and other water based corrosion inhibitors. Dilution of this product by more than 25% with other inhibitor technologies will reduce inhibitor protection performance. Excellent elastomer compatibility.
- **Wide Application** — Recommended for use in internal combustion engines regardless of fuel type where freeze point is not needed and the OEM recommends a nitrite containing, silicate free water based extended life coolant.¹ Delo ELI Corrosion Inhibitor has been successfully used in marine, on-road, off-road and stationary application engines. This product also can be used as an extended life heat transfer fluid in circulating systems.
- **Excellent Protection** — Protects cooling system engine metals including aluminum against erosion, corrosion and cavitation. Silicate free formula shows improved water-pump life over silicate containing coolants.

- **Improved economics** — Low depletion rates helps eliminate need for additional supplemental coolant additives. Delo ELI Corrosion Inhibitor is a super concentrate and should be diluted to 5.5%-10% with good quality water before use.
- **Heat Transfer** — Non deposit forming formula helps maintain heat transfer efficiencies.
- **Environmentally friendly** — At the recommended use rate (5.5 - 10wt% in water), Delo ELI Corrosion Inhibitor has low aquatic toxicity and no long-term effects on the environment. The extended life of the in-use product minimizes the need for frequent disposal, further contributing to the protection of the environment. Undiluted Delo ELI Corrosion Inhibitor concentrate could potentially be harmful to the environment if spilled or improperly disposed, so care should be taken to prevent such releases.
- **Stability** — Shelf life of 1 year. Service life of 6 years minimum.

FEATURES

Delo ELI Corrosion Inhibitor is a water based, extended life corrosion inhibitor based on aliphatic carboxylates that is recommended for use in a wide variety of cooling systems in industrial, on-road, off-road and stationary applications.

Delo ELI Corrosion Inhibitor is recommended where complete cooling system protection is needed but where freeze protection is not required.

APPLICATIONS

Delo ELI Corrosion Inhibitor is recommended for use in industrial and commercial cooling systems where the OEM recommends a silicate free, nitrite containing water based corrosion inhibitor system.

Delo ELI Corrosion Inhibitor is recommended for use in **Caterpillar** and other engine OEM applications where a nitrite containing, silicate free extended life coolant is specified.

¹ Check for specific OEM recommendations.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

20 June 2016
COOL-44

© 2015-2016 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark and Delo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

Toxicological & environmental aspects

At the recommended use rate (5.5 - 10wt% in water), Delo® ELI Corrosion Inhibitor has low aquatic toxicity and no long-term effects on the environment. The extended life of the in-use product minimizes the need for frequent disposal, further contributing to the protection of the environment. Undiluted Delo ELI Corrosion Inhibitor concentrate could potentially be harmful to the environment if spilled or improperly disposed, so care should be taken to prevent such releases.

PRODUCT REFERENCE

Product Number 236541
 SDS Number 38254
 Delo ELI Corrosion Inhibitor - Concentrate

TYPICAL TEST DATA

Delo ELI Corrosion Inhibitor

Technical Characteristics	Method	Delo ELI
Inhibitor content		50% w/w
Water content	ASTM D1123	50% w/w
Amine, phosphate, borate, silicate		None
Color		Red
Specific gravity, 20°C	ASTM D1122	1.08 typ.
pH	ASTM D1287	8.3 typ.
Storage stability		1 year
	Method	5% dilution
pH	ASTM D1287	8.3 typ.
Foaming properties at 25°C	ASTM D1881	55 ml typ.
• break Time		3 sec typ.
Effect on non-metals	GME 60 255	no effect
Hard water stability	VW PV 1426	no precipitate

Minor variations in product typical test data are to be expected in normal manufacturing.

Delo ELI Corrosion Inhibitor

ASTM D1384 Glassware Corrosion Test

	ASTM D3306 (max)	5% Delo ELI Weight loss, mg per coupon ^a
Copper	10 max	1.6
Solder	30 max	-0.3
Brass	10 max	1.7
Steel	10 max	0.2
Cast Iron	10 max	1.5
Aluminum	30 max	4.6

^a Weight loss AFTER chemical cleaning. All weight losses are in mg/coupon. Weight gain is indicated by a "-" sign.

HANDLING PRACTICES

Delo ELI Corrosion Inhibitor is a water based product and will freeze. This product is not combustible. It is recommended that this product be stored indoors to prevent freezing. If freezing occurs product should be defrosted and agitated before use.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.