



Delo® Gold NG

Heavy Duty Mobile Gas Engine Oil

Product Data Sheet

Customer benefits

Alternative fuel performance

Formulated especially for medium and heavy duty vehicles powered by CNG-fuelled engines.

Clean crankcases and top decks

Minimize the formation of sludge in the crankcase and in the valve rocker cover/top deck area.

Prevents corrosion

Good oxidation and nitration resistance help prevent bearing corrosion.

Better piston and ring belt deposit control

Optimised and proven low ash additive system which provide good deposit control throughout the entire engine.

Applications

- Suitable for use in various CNG model engines for standard drain mobile applications

Product features:

- Delo® Gold NG with ISOSYN® Technology is a proven CNG/LNG oil formulated to deliver protection in a wide variety of medium and heavy duty CNG-fuelled applications.



Typical key properties

DELO® GOLD NG		
SAE Grade	15W-40	20W-50
Product Code	500646	500647
Base No., D2896, mg KOH/g	5.41	5.4
Sulfated Ash, mass %	0.58	0.58
Phosphorus, mass %	0.07	0.07
Flash Point, °C	240	266
Pour Point, °C	-33	-33
Viscosity, Kinematic		
mm ² /s @ 40°C	116	170
mm ² /s @ 100°C	15.1	19.1
Viscosity Index	136	127
Zinc, mass %	0.08	0.08

1507

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit: www.CaltexDelo.com

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific