Valor® 300 Multigrade

Heavy-Duty Multigrade Diesel Engine Oil

Product description

Valor 300 Multigrade SAE 20W-50 is a heavy- duty diesel engine oil designed to lubricate diesel engines requiring API CD performance lubricants.

The level of alkaline reserve makes it suitable for use with high sulfur fuels at appropriate oil drain intervals.

Customer benefits

- **Protection for diesel engines**
  Metallo-organic anti-wear additive system forms a protective layer on contact surfaces to reduce wear. Effective corrosion inhibitors protect against corrosive attack on bearings and other engine components.
- **Dependable diesel performance**
  Effective combination of detergent and dispersant additives helps maintain power and performance by resisting piston and ring deposits under high temperature conditions.
- **Reduce maintenance costs**
  Good oxidation stability resists oil degradation and protects against oil thickening, and oil line and filter plugging.

Applications

The following applications whenever the manufacturer recommends SAE 20W-50 viscosity grade oil meeting API CD:

- Diesel engines (high-speed, four-stroke, turbocharged or naturally aspirated).
- Commercial road transport.
- Off-highway vehicles.
- Agricultural tractors.
- High speed diesel engines in marine service (e.g., fishing boats, river transport).
- Generator sets.

Approvals, performance and recommendations

- API CD

A Chevron company product. All trademarks are property owned by Chevron Intellectual Property LLC.

Visit Product Information Center >

Valor® 300 Multigrade

Heavy-Duty Multigrade Diesel Engine Oil

Typical test data

VALOR 300 MULTIGRADE	RESULTS
SAE Grade	**20W-50**
Product Code	**500818**
Kinematic Viscosity, mm^2/s @ 100°C mm^2/s @ 40°C	 19.3 173
Viscosity Index	127
Base No., D2896, mg KOH/g	9.4
Zinc, m %	0.04
Calcium, m %	0.34

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Africa, Middle East and Pakistan.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

Chevron's Family of Brands

A Chevron company product

© 2024 Chevron Products Company. Asia Pacific. All Rights Reserved.