

Havoline® Ultra R

Premium performance, Synthetic, Low SAPS Passenger Car Motor Oil



Product description

Havoline® Ultra R is a premium performance, synthetic multigrade motor oil formulated for use in gasoline and diesel modern passenger car and light truck commercial diesel engines.

Customer benefits and product features

Customer benefits

Help extend lifetime of after-treatment devices

Formulation containing low levels of ash-forming phosphorus and sulphur additives (low SAPS) helps extend DPF and TWC service life.

Long engine life

Metallic detergent and ashless dispersant additive system helps prevent engine failure, even under severe operating conditions, by providing excellent control of ring belt and piston skirt deposits. Excellent low temperature viscosity characteristics help ensure that vital engine components are lubricated quickly at start-up, even at very low temperatures.

Helps reduce maintenance cost

Proven thermal stability and oxidation resistance helps minimise in-service oil degradation which contributes to filter blocking and sludge formation in the oil galleries, crankcase and valve train.

Low oil consumption

Very high viscosity index synthetic base oils help control oil flow through the ring belt area by helping to maintain oil viscosity and reduce oil evaporation at the elevated piston temperatures experienced under even very severe operating conditions.

Product features

Havoline® Ultra R SAE 5W-30 is a low SAPS lubricant, formulated with synthetic base stocks and advanced technology additives offering low levels of sulphated ash, phosphorus and Sulphur

Applications

High performance, naturally aspirated and turbocharged gasoline and light duty diesel engines in modern passenger cars and light commercial vehicles, equipped with modern three-way catalysts (TWC) and diesel particulate filters (PDF) requiring low SAPS oils.

Product approvals, performance and recommendations

Performance standards

- Developed independently by Chevron to comply with ACEA C4
- Approved by the following manufacturers:

MB-Approval 226.51

Renault RN 0720

Consult OEM representatives for independent verification, updates and recommendations.

Havoline® Ultra R

Premium performance, Synthetic, Low SAPS Passenger Car Motor



Typical Test Data

HAVOLINE® ULTRA R KEY PROPERTIES	RESULTS
SAE Grade	5W-30
Product Code	501276
Phosphorus, m %	0.05
Sulphated Ash, m%	0.49
Viscosity,	
mm ² /s @ 40°C	67.1
mm ² /s @ 100°C	11.5
Zinc, m %	0.5

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Havoline® Ultra R/AP/PDSV1_17/08/2023



A Chevron company product

© 2023 Chevron Products Company. Asia-Pacific.
All Rights Reserved.