# Delo® Gear EP-5

SAE 80W-90, 85W-140



## Product description

**Delo® Gear EP-5** are multipurpose lubricants made from paraffinic base stocks and containing a carefully balanced additive package to provide gear protection and long lubricant life.

## Customer benefits and product features

#### **Customer benefits**

Corrosion Delo Gear EP-5 delivers value through:

#### Long gear life

Extreme pressure properties protect hypoid and other types of gears from scuffing and wear.

### Rust and corrosion protection

Effective inhibitor package protects against rusting or corrosion of gear and bearing surfaces.

#### • Excellent foam inhibition

Foaming minimized by use of foam inhibitor.

### Long lubricant life

Outstanding thermal and oxidation stability allow high temperature operation with long lubricant life.

#### Seal Protection

Formulated to protect against oil seal deterioration.

#### **Product features**

- The sulfur-phosphorus extreme pressure additive technology used in Delo Gear EP-5 provides exceptional thermal and oxidation stability. In addition, this lubricant is fortified with rust and corrosion inhibitors, a foam inhibitor, and a pour point depressant
- The sulfur-phosphorus extreme pressure additives in Delo Gear EP-5 minimize the spalling and wear of gears by creating a microthin sacrificial film on the surface of the gear teeth which is actually softer than the gears themselves. Frictional heat and pressures between gear teeth cause the sulfur-phosphorus to react with the surfaces of the gear teeth at the point of contact, thus creating the sacrificial film.
- The highly refined base stocks and various inhibitors in the additive package help assure a well-balanced lubricant and long gear and bearing life.

# Delo® Gear EP-5

SAE 80W-90, 85W-140



## **Applications**

Delo Gear EP-5 are recommended for use in spiral bevel and hypoid differentials, power dividers, and oillubricated steering axle wheel bearings. Their multi viscosity characteristics allow their use in equipment operating over a broad ambient temperature range. This means good cold flow properties and gear protection.

## Approvals, performance and recommendations

## Delo Gear EP-5 are approved for:

- SAE J2360 (formerly known as MIL-PRF-2105E)
- Volvo 97321 Approval
  - o SAE 80W-90 (Approval Nr. 97321-04)
  - SAE 85W-140 (Approval Nr. 97321-06
- ZF Approval
  - o SAE 80W-90 TE-ML 05A, 12M, 16B, 17B, 19B, and 21A (Approval Nr. ZF002270)
  - o SAE 85W-140 TE-ML 05A, 12M, 16D, and 21A (Approval Nr. ZF002254)

### Delo Gear EP-5 meet the requirements of:

- API Service Categories MT-1, and GL-5
- Mack GO-J

## Delo® Gear EP-5

SAE 80W-90, 85W-140



## Typical Test Data

DELO® GEAR EP-5		
SAE Grade	80W-90	85W-140
Product Code	510411	510412
Density @ 15°C	0.894	0.905
Viscosity, Kinematic cSt @ 40°C cSt @ 100°C	140 15.0	344 25.5
Viscosity, Brookfield cP @ -12°C cP @ -26°C	- 126,4000	56,100 -
Viscosity Index	108	97
Flash Point, °C	213	234
Pour Point, °C	-30	-15

2205

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the <u>Product Information Center</u>.

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.