

# Havoline® Motor Oil SAE 10W-40 API SJ

Passenger Car Motor Oil



## Product description

High quality, shear-stable, multigrade engine oil for use in a wide range of passenger car and light-duty commercial vehicle gasoline engines, where API SJ performance lubricants are required. It provides a high level of protection against starting friction, heat stress and engine deposits.

## Customer benefits

- **Long engine life**  
Proven metallo-organic anti-wear additive system resists wear under all operating conditions by forming a protective layer on contact surfaces. Multigrade viscosity provides additional protection against wear at start-up and under high temperature operating conditions as compared with monograde oils of similar performance.
- **Preserves power and performance**  
Metallic detergent and ashless dispersant additive system preserves power and performance by providing good control of piston and ring deposits under high temperature conditions.
- **Saves on maintenance**  
Very good thermal and oxidation stability resists in-service oil degradation that contributes to filter blocking and sludge formation.

## Applications

- Naturally aspirated and turbocharged gasoline engines in passenger cars where API SJ or lower performance oils are specified.
- Light truck gasoline engines where API SJ or lower performance oils are specified.
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils of API SJ or lower performance.

*Not recommended for use in diesel engines, motorcycle engines, or gasoline engines that require API SL or higher performance oils.*

## Approvals, performance and recommendations

- API SJ

# Havoline® Motor Oil SAE 10W-40 API SJ

Passenger Car Motor Oil



## Typical test data

HAVOLINE MOTOR OIL SAE 10W-40	RESULTS
<b>SAE Grade</b>	<b>10W-40</b>
<b>Product Code</b>	<b>500154</b>
Base No., D2896, mg KOH/g D4739, mg KOH/g	5.7 5.5
Phosphorus, m %	0.100
Sulfated Ash, m %	0.8
Viscosity, mm <sup>2</sup> /s @ 40°C mm <sup>2</sup> /s @ 100°C	103.4 15.0
Viscosity Index	152
Zinc, m %	0.11

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Africa, Middle East and Pakistan.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Havoline® Motor Oil SAE 10W-40/PAK/CHV/PDSv1\_072024



**A Chevron company product**

© 2024 Chevron Products Company. Asia Pacific.  
All Rights Reserved.