

# Delo<sup>®</sup> 400 MGX SAE 15W-40

Premium Heavy Duty Diesel Engine Oil



## Product description

**Delo<sup>®</sup> 400 MGX** SAE 15W-40 is an API CJ-4 heavy duty diesel engine oil specifically formulated for on-highway and off-highway applications using either High Sulfur or Low Sulfur Diesel and can also provide protection for newer compliant low emission diesel engines with Selective Catalytic Reduction (SCR), Diesel Particulate Filter (DPF) and Exhaust Gas Recirculation (EGR). It is fully compatible with previous diesel engine models and previous API Oil Service Categories including API CI-4 PLUS, API CI-4 and API CH-4.

**Delo<sup>®</sup> 400 MGX** is specifically formulated for exceptional performance in either high (up to 2000 ppm) or low sulfur diesel fuels and for the latest low emission diesel engines fitted with diesel particulate filters, but also those fitted with EGR and/or SCR systems.

**Delo<sup>®</sup> 400 MGX** is formulated with ISOSYN base oils and high performance low-ash additive technology to provide exceptional soot dispersancy, deposit control and wear protection.

## Customer benefits

### Customer benefits

- **Minimized operating costs**

Exceptional soot dispersancy and wear control. Cylinders, pistons, rings, and injectors are well protected against wear and corrosion, providing optimum service life and minimal maintenance. Contributes to maximum vehicle utilization and minimal downtime.

- **Excellent emission control system life**

Provides optimum Diesel Particulate Filter (DPF) life for minimal downtime and cleaning, thus managing your maintenance costs.

- **Managed inventory costs**

Backward compatible with previous API Oil Service Categories and engine models. Suitable for use in four-stroke gasoline and naturally aspirated, turbocharged and modern electronically controlled / low emission diesel engines calling for an SAE 15W-40 heavy duty motor oil.

# Delo<sup>®</sup> 400 MGX SAE 15W-40

Premium Heavy Duty Diesel Engine Oil



## Applications

Delo 400 MGX SAE 15W-40 is recommended for naturally aspirated and turbocharged four-stroke diesel engines in which the API CJ-4, CI-4 PLUS, CI-4 categories and SAE 15W-40 viscosity grade are required by the manufacturers. It is formulated for engines operating under severe service and a wide range of climatic conditions. This product is recommended for use in:

- Commercial road transport, including the latest engines fitted with exhaust cleanup devices of all types.
- Vehicles meeting the most recent exhaust emissions standards, including US EPA 2002, 2007 and 2010, 2017 greenhouse gas (GHG 17) Euro IV, V and VI, and Australian ADR 80/02 and ADR 80/03 (for heavy duty).
- Mixed fleets of both diesel and gasoline engines, and both old and new equipment.
- Stop-and-go vehicles in high soot loading service such as buses and waste collection trucks.
- Most modern off-highway engines including those adapted for current and future emissions standards in construction, agriculture, marine and mining applications.
- High speed diesel engines using high (up to 2000 ppm) or low sulfur diesel fuels.
- Diesel engines utilizing diesel fuels with up to 35% biodiesel (B35)\*

*Note: \* When using Biodiesel blended fuel meeting ASTM D7467 (B6 – B20) or equivalent and higher blends when blended with B100 as per ASTM D6751 or equivalent. When using >B6 biodiesel it is critical to monitor the engine oil level and performance. Refer OEM recommendation for oil selection and drain intervals when using biodiesel*

## Product approvals, performance, and recommendations

### Approvals:

- API CJ-4, CI-4 PLUS, CI-4, CH-4 / SM
- Detroit Diesel 93K218
- Daimler DTFR 15C100 (previously known as MB 228.31)
- DEUTZ DQC III-18 LA
- Mack EO-O Premium Plus
- MTU Category 2.1
- Renault RLD-3
- Volvo VDS-4
- ZF TE-ML 04C

### Meets the Requirements of:

- ACEA E7, E9-16
- Caterpillar ECF-3, ECF-2
- Ford WSS-M2C171-E
- MAN M 3575

Suitable for use where oils meeting JASO DH-2 specification are recommended

Suitable for use in applications requiring oils meeting Cummins CES 20081 in engines under 50 liters displacement

# Delo<sup>®</sup> 400 MGX SAE 15W-40

Premium Heavy Duty Diesel Engine Oil



## Typical test data

Delo <sup>®</sup> 400 MGX SAE 15W-40	Test Method	Results
<b>SAE Grade</b>		<b>15W-40</b>
<b>Product Code</b>		<b>500634</b>
Base No., mg KOH/g	ASTM D2896	9.9
Base No., mg KOH/g	ASTM D4739	8.0
Sulfated Ash, m %	ASTM D784	1.0
Kinematic viscosity, mm <sup>2</sup> /s @ 40°C mm <sup>2</sup> /s @ 100°C	ASTM D445	120
	ASTM D445	14.6
Viscosity Index	ASTM D2270	134

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, [Visit Product Information Center >](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Delo 400 MGX 15W-40/Asia Pacific/CHV/PDSv1\_03/2024



**A Chevron company product**

© 2024 Chevron Products Company. Asia-Pacific.  
All Rights Reserved.