



# URSA<sup>®</sup> SUPER PLUS EC

## SAE 15W-40

---

### PRODUCT DESCRIPTION

Ursa<sup>®</sup> Super Plus EC SAE 15W-40 is a heavy duty engine oil recommended for all naturally aspirated and turbocharged four-stroke diesel engines and four-stroke gasoline engines in which the API CK-4 or API SN service categories and SAE 15W-40 viscosity grades are recommended.

### CUSTOMER BENEFITS

Ursa Super Plus EC SAE 15W-40 is an API CK-4 heavy duty engine oil specifically formulated for 2017 greenhouse gas (GHG 17) compliant diesel engines designed to meet lower CO<sub>2</sub> emissions and improved fuel economy, in addition to 2010 compliant low emission diesel engines with Selective Catalytic Reduction (SCR), Diesel Particulate Filter (DPF) and Exhaust Gas Recirculation (EGR) systems calling for SAE 15W-40 heavy duty engine oil. It is fully compatible with previous engine models and previous API Oil Service Categories.

Ursa Super Plus EC SAE 15W-40 delivers value through:

- **Good Engine Protection** — Disperses soot and helps control wear. Cylinders, pistons, rings, and valve train components are well protected against wear and corrosion, providing good service life and minimal maintenance.
- **Appropriate Emission Control System Life** — Provides appropriate Diesel Particulate Filter (DPF) life for minimal downtime and cleaning, thus managing maintenance costs.
- **Managed Inventory Costs** — Backward compatible with all previous API Oil Service Categories and engine models. Good for service in gasoline engines and naturally aspirated, turbocharged and modern electronically controlled/low emission diesel engines.

Product(s) manufactured in the USA and Colombia.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 September 2018  
HDMO-95

© 2008-2018 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark and Ursa are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

- **Access to Chevron's Lubrication and Industry Knowledge** - Helps maximize your bottom line business results.

### FEATURES

Ursa Super Plus EC SAE 15W-40 is a cost effective fleet heavy duty engine oil formulated to provide appropriate protection in normal operating conditions. It is designed to be a cost effective formulation for multiple types of applications.

### APPLICATIONS

Ursa Super Plus EC SAE 15W-40 is a heavy duty engine oil recommended for four-stroke diesel and gasoline engines in which API CK-4 or API SN service category and SAE 15W-40 viscosity grades are recommended. It is formulated for engines operating under severe service and a wide range of climatic conditions.

**Ursa Super Plus EC SAE 15W-40 is approved for:**

- **API Service Categories** CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4 and SN
- **Cummins** CES 20081
- **Mack** EO-O Premium Plus
- **Volvo** VDS-4

**Ursa Super Plus EC SAE 15W-40 is recommended for:**

- **Caterpillar** ECF-3

## TYPICAL TEST DATA

<b>SAE Grade</b>	<b>15W-40</b>
<i>Product Number</i>	257005
<i>SDS Number</i>	
<i>U.S.</i>	43290
<i>Canada</i>	43291
<i>Mexico</i>	43292
<i>Colombia</i>	46317
Density at 15°C, kg/L	0.8779
Viscosity, Kinematic	
mm <sup>2</sup> /s at 40°C	105.3
mm <sup>2</sup> /s at 100°C	14.5
Viscosity, Cold Crank, °C/mPa.s	-20/5700
Viscosity, MRV, °C/mPa.s	-25/15,600
Viscosity, HTHS, mPa.s at 150°C	4.1
Viscosity Index	140
Flash Point, °C(°F)	230(446)
Pour Point, °C(°F)	-36(-33)
Sulfated Ash, mass %	1.0
Base Number, ASTM D2896, mgKOH/g	8.7
Sulfur, mass %	0.259
Phosphorus, mass %	0.077
Zinc, mass %	0.086

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.