



DELO[®] GEAR EP-5

SAE 80W-90, 85W-140

PRODUCT DESCRIPTION

Delo[®] Gear EP-5 gear lubricants are recommended for use in spiral bevel and hypoid differentials, power dividers, and oil-lubricated steering axle wheel bearings.

CUSTOMER BENEFITS

Delo Gear EP-5 delivers value through:

- **Long gear life** — Extreme pressure properties protect hypoid and other types of gears from scuffing and wear.
- **Rust and corrosion protection** — Effective inhibitor package protects against rusting or corrosion of gear and bearing surfaces.
- **Excellent foam inhibition** — Foaming minimized by use of foam inhibitor.
- **Long lubricant life** — Outstanding thermal and oxidation stability allow high temperature operation with long lubricant life.
- **Seal Protection** — Formulated to protect against oil seal deterioration.

FEATURES

Delo Gear EP-5 are multipurpose lubricants.

They are made from paraffinic base stocks and contain a carefully balanced additive package to provide gear protection and long lubricant life.

The sulfur-phosphorus extreme pressure additive technology used in Delo Gear EP-5 provides exceptional thermal and oxidation stability. In addition, this lubricant is fortified with rust and corrosion inhibitors, a foam inhibitor, and a pour point depressant.

The sulfur-phosphorus extreme pressure additives in Delo Gear EP-5 minimize the spalling and wear of gears by creating a microthin sacrificial film on the surface of the gear teeth which is actually softer than the gears themselves. Frictional heat and pressures between gear teeth cause the sulfur-phosphorus to react with the surfaces of the gear teeth at the point of contact, thus creating the sacrificial film.

The highly refined base stocks and various inhibitors in the additive package help assure a well-balanced lubricant and long gear and bearing life.

APPLICATIONS

Delo Gear EP-5 lubricants are recommended for use in spiral bevel and hypoid differentials, power dividers, and oil-lubricated steering axle wheel bearings.

Their multiviscosity characteristics allow their use in equipment operating over a broad ambient temperature range. This means good cold flow properties and gear protection.

Delo Gear EP-5 lubricants are approved for **SAE J2360** (formerly known as MIL-PRF-2105E) and Volvo 97321. It meets the requirements of:

- **API Service Categories** MT-1 and GL-5
- **Mack** GO-J
- **Meritor** 076-D (SAE 80W-90)
- **Meritor** 076-A (SAE 85W-140)
- **ZF** TE-ML 05A, 12M, 16B, 17B, 19B, 21A (SAE 80W-90)
- **ZF** TE-ML 05A (SAE 85W-140)

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 February 2022
GL-46

© 2017-2022 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark and Delo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

TYPICAL TEST DATA

SAE Grade	Test Method	80W-90	85W-140
<i>Product Number</i>		223022	223021
<i>SDS Number</i>			
<i>U.S.</i>		44036	44036
<i>Canada</i>		44042	44042
<i>Mexico</i>		44043	44043
Density at 15.6°C, kg/L Density at 60°F, lb/gal	ASTM D4052	0.8856(7.39)	0.8991(7.50)
Viscosity, Kinematic cSt at 40°C cSt at 100°C	ASTM D445	145 14.2	341 25.0
Viscosity, Brookfield cP at -12°C cP at -26°C	ASTM D2983	— 73,000	80,000 —
Viscosity Index	ASTM D2270	95	95
Flash Point, °C(°F)	ASTM D92	218(421)	226(439)
Pour Point, °C(°F)	ASTM D97	-33(-27)	-15(+5)

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.