Super Generator Engine Oil SAE 15W-40

High Speed Diesel Engine Generator Oil

Product description

High performance, multigrade oil specifically designed to lubricate high speed diesel engines for generator sets requiring API CI-4 or Global DHD-1 performance lubricants.

Customer benefits

- **Preserves full power and performance**
  Carefully balanced detergent additive system preserves full power and performance by providing excellent upper-ring-belt deposit control under the high temperatures encountered in turbocharged diesel engines.

- **Extends oil and filter service intervals**
  Highly effective additive system minimizes the formation of sludge which can lead to premature oil thickening and filter plugging.

- **Reduces maintenance costs**
  A combination of high quality base fluids and balanced metallic detergent and ashless dispersant additive system, provides excellent overall engine cleanliness in all service conditions.

- **Prolongs engine life**
  Effective anti-wear additive system provides excellent protection against wear of critically loaded components under severe operating conditions. Multigrade viscosity provides additional protection against wear at start-up and under high temperature operating conditions.

A Chevron company product. All trademarks are property owned by Chevron Intellectual Property LLC.

Visit Product Information Center >

Super Generator Engine Oil SAE 15W-40

High Speed Diesel Engine Generator Oil

Applications

- High speed, four-stroke, turbocharged or naturally aspirated diesel engines for generator sets in stand-alone / back up or continuous operations such as in commercial service or Mobile Telecom Towers.
- Diesel engines for generator sets requiring oils meeting Caterpillar ECF-1-a, Volvo VDS-3 or Cummins CES 20076 / 77 / 78 standards.

Approvals, performance and recommendations

- API CI-4, CH-4 /SL
- Global DHD-1
- Caterpillar ECF-1-a
- Volvo VDS-3
- Cummins CES 20076 / 77 / 78 (planned)

Meets the Requirements of:

- API CF-4, CF, CD

A Chevron company product. All trademarks are property owned by Chevron Intellectual Property LLC.

Visit Product Information Center >

Super Generator Engine Oil SAE 15W-40

High Speed Diesel Engine Generator Oil

Typical test data

SUPER GENERATOR ENGINE OIL	RESULTS
SAE Grade	**15W-40**
Product Code	**500633**
Viscosity, ASTM D445	
mm^2/s @ 40°C	115
mm^2/s @ 100°C	15
Viscosity Index, ASTM D2270	137
Base No., ASTM D2896, mg KOH/g	9.6
Zinc, ASTM D4951, m %	0.11
Calcium, ASTM D4951, m%	0.33
Flash Point, COC, ASTM D92, °C, min	215
Pour Point, ASTM D97, °C, max	-25

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Africa, Middle East and Pakistan.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

Chevron's Family of Brands

A Chevron company product

© 2024 Chevron Products Company. Asia Pacific. All Rights Reserved.