

Delo Syn-TDL SAE 75W-90

Premium performance fully synthetic Total Driveline Lubricant

Product description

Delo® Syn-TDL SAE 75W-90 is a premium performance fully synthetic Total Driveline Lubricant offering extended drain capability, designed for API GL-4 and API GL-5 applications, and offers good thermal stability in higher temperature operations.

Delo Syn-TDL SAE 75W-90 is formulated with fully synthetic base oils in combination with an advanced high performance additive system.

Customer benefits

- Specially tuned friction characteristics make the product suitable for use in many synchronised manual transmissions and final drives, allowing inventory rationalisation
- Offers significantly longer service than conventional mineral gear oils in many applications - up to twice as long in transmissions and three times as long in drive axles
- Long-drain capability helps reduce overhaul and maintenance downtime
- High performance advanced additive system provides reliable extreme pressure protection and wear resistance
- Low-temperature fluidity offers component protection by allowing rapid oil circulation during cold weather start-up
- High Viscosity Index and good shear stability help provide viscosity and film thickness sufficient for effective high temperature lubrication throughout fluid service life



Product highlights

- Suitable for many synchronised manual transmissions and final drives
- Long-drain capability
- Offers extended service capabilities
- Provides reliable EP protection and wear resistance
- Offers rapid oil circulation during cold start-up
- High Viscosity Index and good shear stability

Selected specification standards include:

API	Bosch
DAF	Detroit Diesel
MAN	Daimler Truck
NATO	SAE
Scania	Volvo
ZF	

Applications

- Delo Syn-TDL SAE 75W-90 is designed for use in automotive manual transmissions and hypoid drive axles which require a fluid with API GL-4, GL-5 or MT-1 performance. It is approved against standard SAE J2360 (former MIL-PRF-2105E).
- The thermal stability makes Delo Syn-TDL SAE 75W-90 suitable for use in applications with higher operating temperatures than is possible when using mineral gear oils. The special characteristics of the synthetic base oils lead to a reduction in the operating temperature, further extending the service capability in arduous operating conditions, or improving fuel economy in normal service conditions. It is capable of significantly longer service intervals than conventional mineral gear oils in many applications: up to twice as long in transmissions and more than three times as long in drive axles.
(The precise service interval varies according to application and service severity – refer to the manufacturers' literature for further details).
- Delo Syn-TDL SAE 75W-90 is not recommended for use in ZF transmissions fitted with intertarders (this includes some models from constructors such as DAF and MAN). For these exceptions, use an approved fluid such as Delo Syn-MTF XZ 75W-80.

Approvals, performance and suitable for use

Approvals

• Daimler Truck	DTFR 12B140 (Previously MB 235.8)
• Detroit Diesel	DFS Axle Gear Oil Specification 93K219.01
• MAN	341 Type Z2 ^[15]
• MAN	342 Type S1 ^[15]
• MAN	341 GA1 ^[15]
• SAE	J2360 ^[2]
• Scania	STO 1:1G
• Scania	STO 2:0 A FS
• Volvo	97312 ^[13]
• ZF	TE-ML 02B ^[4]
• ZF	TE-ML 05A ^[4]
• ZF	TE-ML 12L ^[4]
• ZF	TE-ML 12N ^[4]
• ZF	TE-ML 16F ^[4]
• ZF	TE-ML 17B ^[4]
• ZF	TE-ML 19C ^[4]
• ZF	TE-ML 21A ^[4]

Performance

• API	GL-4
• API	GL-5
• API	MT-1
• Bosch	TE-ML 08 ^[12]
• DAF	Gearbox oil for Eaton gearboxes ^[5]
• DAF	Gearbox oil for ZF gearboxes ^[1]
• DAF	Rear axle without hub reduction ^[6]
• DAF	Rear axle with hub reduction ^[7]
• MAN	3343 Type S ^[8]
• NATO	0-226
• Scania	STO 1:0 ^[3]
• ZF	TE-ML 07A ^[9]
• ZF	TE-ML 12B ^[10]

Suitable for use

• MAN	341 Type E3 ^[14]
• ZF	TE-ML 05B ^[11]
• ZF	TE-ML 21B ^[11]

[1] ZF gearboxes without intertarder, standard changing interval.

[2] Approval number: PRI GL 0620.

[3] Axles in light- and medium-loaded long-distance applications (operation types 0:0, 0 and 1). Other axle applications require higher viscosity fluids.

[4] ZF registration number: ZF003353.

[5] Eaton gearbox applied in vehicle series LF45/55, 65/75/85 CF, CF 65/75/85; extended changing interval.

[6] Except for type V200/V400 (requires an SAE 85W-140 oil). Extended changing interval.

[7] Except for type 1356 (requires special product). Standard changing interval.

[8] Formerly approved. MAN 3343 Type S is now obsolete and has been replaced by 341 Type E3 (now obsolete) and 341 Type Z2 (manual transmissions), and 342 S1 (axles and transfer cases).

[9] Products meeting the necessary performance requirements are approved for use by ZF, but there is no product listing.

[10] ZF has transferred this approval from TE-ML 12B to a new class, TE-ML 12N, which is a higher performance level.

[11] In April 2017, ZF combined class TE-ML 05B with class TE-ML 05A, and class TE-ML 21B with class TE-ML 21A.

[12] List formerly administered by ZF. Products meeting the necessary performance requirements are approved for use, but there is no product listing.

[13] Volvo approval number: 039.

[14] The product meets all of the requirements, but MAN made this specification obsolete at the end of 2016.

[15] MAN approval number: TUC 3419/97.

Typical test data		
Test	Test Methods	Results
Shelf Life: 60 months from date of filling indicated on the product label.		
Viscosity, Kinematic, 100°C, mm²/s	ASTM D445	14.7
Viscosity, Kinematic, 40°C, mm²/s	ASTM D445	98
Viscosity, Brookfield, -40°C, mPa.s	ASTM D2983	56,000
Viscosity Index	ASTM D2270	157
Density, 15°C, kg/l	ASTM D4052	0.868
Flash Point COC, °C	ASTM D92	202
Pour Point, °C	ASTM D5950	-54

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. (1122
may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A Chevron company product