



DELO[®] GEAR EP-5 ISOCLEAN[®] CERTIFIED LUBRICANT SAE 80W-90, 85W-140

PRODUCT DESCRIPTION

Delo[®] Gear EP-5 ISOCLEAN[®] Certified Lubricants are recommended for use in spiral bevel and hypoid differentials, power dividers, and oil-lubricated steering axle wheel bearings. Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



CUSTOMER BENEFITS

Delo Gear EP-5 ISOCLEAN Certified Lubricants deliver value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.
- **Long gear life** — Extreme pressure properties protect hypoid and other types of gears from scuffing and wear.
- **Rust and corrosion protection** — Effective inhibitor package protects against rusting or corrosion of gear and bearing surfaces.
- **Excellent foam inhibition** — Foaming minimized by use of foam inhibitor.

- **Long lubricant life** — Outstanding thermal and oxidation stability allow high temperature operation with long lubricant life.
- **Seal Protection** — Formulated to protect against oil seal deterioration.

FEATURES

Delo Gear EP-5 ISOCLEAN Certified Lubricants are multipurpose lubricants.

They are made from paraffinic base stocks and contain a carefully balanced additive package to provide gear protection and long lubricant life.

The sulfur-phosphorus extreme pressure additive technology used in Delo Gear EP-5 ISOCLEAN Certified Lubricants provide exceptional thermal and oxidation stability. In addition, this lubricant is fortified with rust and corrosion inhibitors, a foam inhibitor, and a pour point depressant.

The sulfur-phosphorus extreme pressure additives in Delo Gear EP-5 ISOCLEAN Certified Lubricants minimize the spalling and wear of gears by creating a micro-thin sacrificial film on the surface of the gear teeth which is actually softer than the gears themselves. Frictional heat and pressures between gear teeth cause the sulfur-phosphorus to react with the surfaces of the gear teeth at the point of contact, thus creating the sacrificial film.

The highly refined base stocks and various inhibitors in the additive package help assure a well-balanced lubricant and long gear and bearing life.

Product(s) manufactured in the USA and Colombia.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 January 2019
GL-46 ISOCLEAN

© 2019 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark and Delo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

APPLICATIONS

Delo Gear EP-5 ISOCLEAN Certified Lubricants are recommended for use in spiral bevel and hypoid differentials, power dividers, and oil-lubricated steering axle wheel bearings.

Their multiviscosity characteristics allow their use in equipment operating over a broad ambient temperature range. This means good cold flow properties and gear protection.

Delo Gear EP-5 ISOCLEAN Certified Lubricants are approved for **SAE J2360** (formerly known as MIL-PRF-2105E) and meet the requirements of:

- **API Service Categories** MT-1, GL-4 and GL-5
- **Mack GO-J**

Consult with your Chevron Lubricant Representative or Chevron ISOCLEAN Certified Lubricants Marketer to set specific ISO Cleanliness targets for your business application.

TYPICAL TEST DATA

SAE Grade	80W-90	85W-140
Product Number	223026	223025
SDS Number		
U.S.	44036	44036
Canada	44042	44042
Mexico	44043	44043
Colombia	47698	47698
Density at 15.6°C(60°F), kg/L(lb/gal)	0.8856(7.39)	0.8991(7.50)
Viscosity, Kinematic		
cSt at 40°C	145	341
cSt at 100°C	14.2	25.0
Viscosity, Brookfield		
cP at -12°C	—	80,000
cP at -26°C	73,000	—
Viscosity Index	95	95
Flash Point, °C(°F)	218(421)	226(439)
Pour Point, °C(°F)	-33(-27)	-15(+5)

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.