



SUPREME MOTOR OIL ISOCLEAN® CERTIFIED LUBRICANT SAE 10W-30

PRODUCT DESCRIPTION

Supreme ISOCLEAN® Certified Lubricant SAE 10W-30 is a premium quality motor oil that protects against harmful deposits, sludge and contamination in automotive engine applications. Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



- Help prevent Low Speed Pre-Ignition (LSPI) in turbocharged direct-injection engines.
- Help maximize the life of catalytic converters / emissions control systems.
- Slow the aging process by reducing wear to keep engines running longer.

PERFORMANCE CLAIMS

- Keeps engines clean through sludge prevention and limits deposit formation better than industry standard
- Excellent three-way catalyst protection
- Reduces friction-related wear up to 25% better than GF-6 limit¹.

1. Based on Sequence IVB valvetrain wear test using SAE 0W-30

FEATURES/BENEFITS

Supreme ISOCLEAN Certified Lubricant SAE 10W-30 delivers value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.

Supreme ISOCLEAN Certified Lubricant SAE 10W-30 is specifically formulated with quality base oils and cutting-edge additives to:

- Help maximize the power of your engine while maintaining cleanliness.
- Deliver good protection against sludge and deposit formation under both normal and challenging driving conditions.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

20 April 2021
PCMO-20 ISOCLEAN

© 2020-2021 Chevron U.S.A. Inc. All rights reserved.

Chevron and the Chevron Hallmark are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

APPLICATIONS, SPECIFICATIONS & APPROVALS

Suitable for both new and high-mileage cars, as well as turbocharged and naturally aspirated engines. Primarily for older engines that specify legacy API specifications (SN Plus, SN, SL, SJ, SG, SF).

Meets or exceeds the following industry and OEM standards:

SAE Grade	10W-30
API SP/SN Plus	X
API SP/SN Plus/ Resource Conserving	X
ILSAC GF-6A	X
Chrysler MS-6395	X
Fiat 9.55535-CR-1	X
GM 6094M	X

TYPICAL TEST DATA

SAE Grade	Test Method	10W-30
<i>Product Number</i>		274315
<i>SDS Number</i> U.S. Canada Mexico		17483 17483CAN 17483MEX
Density at 15°C, kg/l	ASTM D4052	0.8726
Viscosity, Kinematic mm ² /s at 40°C mm ² /s at 100°C	ASTM D445 ASTM D445	69.0 10.3
Viscosity, Cold Crank (CCS) (cP), CCS @ °C	ASTM D5293	-25/6500
Viscosity Index	ASTM D2270	136
Flash Point, °C(°F)	ASTM D92	236(457)
Sulfated Ash, wt %	ASTM D874	0.8
Phosphorus, wt %	ASTM D4951	0.067
Zinc, wt %	ASTM D4951	0.075

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.