



Havoline SuperMatic 4T Fully Synthetic

High Performance Premium Four-Stroke Motorcycle Oil

Product Data Sheet

Customer benefits

Performs and protects during every ride

High quality, fully synthetic Group III base oils are selected to ensure the oil retains its intended properties between each service interval.

Tailored for high performance scooters

Recognising the higher engine temperatures seen in larger capacity scooters, Havoline has developed its fully synthetic scooter engine oil with high thermal stability to ensure the engine is protected against damage caused by heat.

Consistent clutch performance

Enhanced frictional properties delivers increased clutch grip for scooters with wet clutch gearboxes, making for a smoother and more enjoyable ride through stressful city riding conditions.

Excellent cleaning properties

Outstanding oxidation protection helps to control oil degradation and the formation of deposits.

Applications

- Modern air- and liquid-cooled four-stroke scooter engines
- Suitable for high performance four-stroke scooter
- Scooters with exhaust catalytic converters
- Scooters with combined engine and transmission units, or separate gearboxes where a multi-grade JASO MA or MA2 engine oil is specified
- Not recommended for use in scooters where a multi-grade JASO MB engine oil is specified

Product features:

- **Havoline® SuperMatic 4T Fully Synthetic** is a premium fully synthetic oil formulated with Havoline **C.O.R.E.+ Technology** that caters to today's modern four-stroke scooters.
- **Havoline C.O.R.E.+ Technology** delivers four key benefits:
 - Cleans and protects – maintains efficient engine performance
 - Oxidation stability – protects against oil degradation
 - Reduces engine heat damage – delivers continuous and superior oil stability
 - Enhances fuel economy – improves efficiency for a smoother ride
- Havoline scooter oils ensure your scooter always performs at its best.



Typical key properties

HAVOLINE SUPERMATIC 4T FULLY SYNTHETIC

SAE Grade	5W-40
Product Code	500728
Base no. (D2896, mgKOH/g)	7.6
Pour Point, °C	-39
Sulphated Ash, m%	0.9
Viscosity, mm ² /s @ 100°C	14.2
Phosphorus, m%	0.08

Performance standards

1. T903:2016 JASO MA2
JASO Identification Number : M065CVX262 (SAE 5W-40)
2. Meets the specifications of API SN

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.chevronlubricants.com.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Global Lubricants
– Asia Pacific