



DELO[®] GEAR ESI[®] ISOCLEAN[®] CERTIFIED LUBRICANT SAE 80W-90, 85W-140

PRODUCT DESCRIPTION

"Delo. Let's go further.[®]"

Delo[®] Gear ESI[®] ISOCLEAN[®] Certified Lubricants are premium grade automotive gear lubricants designed for gears operating under severe temperature and load conditions, and whose SAE 80W-90 viscosity grade offers extended-drain performance comparable to leading synthetics.

Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



- **Seal compatibility** — Seal materials are not adversely affected by Delo Gear ESI at temperatures as high as 163°C (325°F).
- **Low operating temperatures** — Unique additive chemistry minimizes friction resulting in cool operating temperatures.
- **Long lubricant life** — The outstanding thermal and oxidation stability characteristics of Delo Gear ESI allow for optimal drain intervals which may result in lubricant savings.
- **Fuel savings** — The remarkable low friction properties of this product contribute to minimal energy consumption.
- **Compatibility** — Compatible with conventional sulfur-phosphorus and synthesized hydrocarbon based lubricants.

CUSTOMER BENEFITS

Delo Gear ESI ISOCLEAN Certified Lubricants deliver value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.
- **Minimal wear** — Delo Gear ESI are formulated to promote long life for gears, bearings, and seals.

FEATURES

Delo Gear ESI ISOCLEAN Certified Lubricants are premium grade automotive gear lubricants.



They are formulated with ISOSYN[®] Technology and compounded with a unique extreme pressure additive utilizing an inorganic borate compound. They also contain a patented, synergistic combination of additives that protect against wear, seizure, oxidation, corrosion, rust, and foam.

Delo Gear ESI ISOCLEAN Certified Lubricants are ideally suited for gear sets exposed to extremely high temperatures and loads.

Tests have proven that Delo Gear ESI ISOCLEAN Certified Lubricants provide a wear protection film 3 to 5 times thicker than the conventional sulfur-phosphorus antiwear film. The inorganic borate film is

Product(s) manufactured in Colombia.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

21 November 2022
GL-11 ISOCLEAN

© 2019-2022 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Delo, Delo. Let's go further., ESI, ISOSYN and the ISOSYN logo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

composed of compounds that do not react with metal. The film forms promptly to provide exceptional gear protection and maximum thermal stability. By minimizing friction, cool operating temperatures have been observed.

APPLICATIONS

These lubricants are excellent automotive gear lubricants, particularly those operating under severe temperature and load conditions. They provide excellent wear control even in the presence of small amounts of water. Their exceptional thermal and oxidation stability, and antiwear performance promote long gear life and optimal drain intervals.

Delo® Gear ESI® ISOCLEAN® Certified Lubricant **SAE 80W-90** was field tested in more than 100 on-highway, Class 8 trucks with drain intervals of 500,000 to 750,000 miles. The product showed excellent field

results in axles manufactured by **Dana, Meritor, and Mack**. It is approved for the extended drain specifications of both **Meritor** and **Mack**.

Delo Gear ESI ISOCLEAN Certified Lubricants:

- meet the performance requirements of **API Service Categories** GL-4, GL-5, and MT-1
- are qualified for **SAE J2360** (formerly known as MIL-PRF-2105E)
- are approved for **Meritor** O-95 and O-76* extended drain, up to 500,000 mile initial and service fill**
- SAE 80W-90 is approved for **Mack** GO-J PLUS up to 500,000 mile initial and service fill**

Consult with your Chevron Lubricant Representative or Chevron ISOCLEAN Certified Lubricants Marketer to set specific ISO Cleanliness targets for your business application.

TYPICAL TEST DATA

SAE Grade	80W-90	85W-140
Product Number	224605	224606
SDS Number		
U.S.	6698	6698
Canada	6698CAN	6698CAN
Mexico	6698MEX	6698MEX
Density at 15°C, kg/L	0.8882	0.9013
Viscosity, Kinematic		
cSt at 40°C	140	341
cSt at 100°C	14.2	25.0
Viscosity, Brookfield		
cP at -12°C	—	80,000
cP at -26°C	120,000	—
Viscosity Index	99	95
Flash Point, °C(°F)	210(410)	210(410)
Pour Point, °C(°F)	-33(-27)	-15(+5)
Timken OK Load, lb	75	75

Minor variations in product typical test data are to be expected in normal manufacturing.

**Meritor O-95 supersedes O-76 and is backwards compatible.

**Refer to manufacturer's recommendations for extended drain lubricants.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.