

Havoline® Extra SAE 15W-40

Synthetic Blend Passenger Car Motor Oil



Product description

Havoline® Extra SAE 15W-40 is a high performance, higher ash synthetic blend passenger car oil designed to meet ACEA A3/B4 specifications, and critical original equipment manufacturers (OEM) requirements.

Havoline Extra SAE 15W-40 is a premium base oil formulation in combination with latest generation viscosity index (VI) improver, offering optimum wide temperature engine protection.

Customer benefits

- **Maximum engine life**
Formulated with advanced cleaning additives, designed to minimize harmful deposits and sludge build up, helping to extend engine life.
- **Maximum engine protection**
Premium base oils in combination with innovative VI improver offers good wide temperature engine protection. Robust year-round protection with reliable wear and corrosion resistance in high temperature conditions.
- **Excellent performance in highway and stop-start city driving**
Formulation designed for high-speed highway and arduous stop-start city driving conditions where engine temperatures become high.
- **Minimum maintenance costs**
High performance formulation helps improve vehicle uptime through extended oil drain and maintenance periods.

Havoline® Extra SAE 15W-40

Synthetic Blend Passenger Car Motor Oil



Applications

- Both diesel and gasoline passenger cars requiring the latest ACEA A3/B4 and ACEA A3/B3 or API SN.
- Can be used where oils recommended meeting prior API SM / SL / SJ / SH / SG.
- Year-round use in high performance gasoline passenger car engines and light can diesel engines without diesel particulate filter (DPF). For severe operating conditions where extended drain intervals are specified by the manufacturers.
- Recommended for VW DI engines without pump injectors and without diesel particulate filters (DPF).

Approvals, performance and recommendations

Performance standards

- Volkswagen VW 501 01 / 505 00 (licensed)

Meets specifications of:

- ACEA A3/B3
- ACEA A3/B4
- API SN/CF
- Daimler MB 229.1

Havoline® Extra SAE 15W-40

Synthetic Blend Passenger Car Motor Oil



Typical test data

HAVOLINE® EXTRA SAE 15W-40	RESULTS
SAE Grade	15W-40
Product Code	500130
Base No., D2896, mg KOH/g	10.6
Phosphorus, m %	0.11
Sulfated Ash, m %	1.4
Viscosity, mm ² /s @ 100°C	14.4
Zinc, m %	0.12
Viscosity Index	135

ENVIRONMENT, HEALTH, and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions, and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the Product Information Center.

This Product Data Sheet (PDS) was produced for the Africa, Middle East and Pakistan region in good faith from the best information available at the time of issue. The specific information included may not directly reflect the local market or conditions. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. For the most up-to-date, country-specific information, please contact your local customer service center.

This document includes registered and unregistered trademarks, service marks, logos and trade names owned by Chevron Intellectual Property LLC and/or its affiliates, or owned by third parties whose products, services or standards are referred to. You must not use any trademark that appears in this document without permission from the relevant owner.

[Visit Product Information Center >](#)

HAVOLINE® EXTRA SAE 15W-40/MEA/CHV/PDSv1_11/03/2020



Chevron company product

© 2025 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.