

Product Data Sheet



Customer benefits

Enhances acceleration

ZOOMTECH delivers better oil frictional properties to improve clutch grip and enhance acceleration. High static friction prevents clutch slippage, ensuring maximum power transfer, especially under high load conditions.

Reliable protection in city conditions

The base oil's thermal stability, together with a high performance additive package, ensures the engine is constantly protected against wear and damage, and can handle the stressful conditions of stop-and-go city traffic.

Consistent and durable performance

A carefully selected mix of Group II and Group III base oils ensures excellent durability between each service interval.

Keeps clean and stays clean

Our proprietary formulation delivers outstanding oxidation protection and detergency, and protects and keeps your engine clean and running smoothly.

Applications

- · Modern air- and liquid-cooled four-stroke motorcycle engines
- Suitable for modern engines that require low viscosity oils for better fuel efficiency and overall engine response (SAE 10W-30)
- Suitable for modern engines that require added protection and improved wear resistance (SAE 10W-40)
- · Motorcycles with back torque limiters
- Motorcycles with exhaust catalytic converters
- Motorcycles with combined engine and transmission units, or separate gearboxes where a multi-grade JASO MA or JASO MA2 engine oil is specified
- SAE 10W-30 viscosity grade is recommended by Honda
- SAE 10W-40 viscosity grade is recommended by Yamaha, Suzuki, and Kawasaki





• Havoline[®] Super 4T Semi-Synthetic is a high quality semi-synthetic oil with Havoline C.O.R.E.+ Technology, proven in the streets for urban riders who demand a strong and reliable oil for their trusted motorcycles.

• Havoline C.O.R.E.+

Technology delivers four key benefits:

- Cleans and protects – maintains efficient engine performance
- Oxidation stability - protects against oil degradation
- Reduces engine heat damage – delivers continuous and superior oil stability
- Enhances acceleration improves clutch grip under high loads with **ZOOMTECH**
- Havoline motorcycle oils ensure your motorcycle always performs at its best.



A Chevron company product





2009



Typical key properties

HAVOLINE SUPER 4T SEMI SYNTHETIC		
SAE Grade Product Code	10W-30 500724 7.6	10W-40 500725 7.7
Base no. (D2896, mgKOH/g) Pour Point, °C Sulphated Ash, m%	-39 0.7	-39 0.9
Viscosity, mm²/s @ 100°C Phosphorus, m%	9.9 0.08	13.2 0.08

Performance standards

- 1. T903:2016 JASO MA2 JASO Identification Number : M065CVX208 (SAE 10W-30) M065CVX215 (SAE 10W-40)
- 2. Meets the specifications of API SN

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltex.com.

For more information, go to www.caltex.com