



Havoline ProDS V SAE 0W-30

Premium performance synthetic engine oil

Product description

Havoline® ProDS V SAE 0W-30 is a premium performance synthetic engine oil specifically formulated with advanced technology additives to meet Volkswagen-Audi 504.00/507.00 and Porsche C30 engine lubrication requirements.

Havoline ProDS V SAE 0W-30 is suitable for use in gasoline and diesel passenger car, and light duty commercial diesel engines. It is a mid SAPS oil compatible with diesel particulate filters (DPF) and three-way catalysts (TWC).

Customer benefits

- Suitable for a wide range of Volkswagen/Audi gasoline and diesel passenger cars and light diesel vans, with or without turbochargers
- Synthetic formulation with advanced additive technologies promote engine wear protection, performance and uptime
- Mid SAPS technology offers TWC and DPF protection, helping reduce exhaust emissions
- Low temperature fluidity helps ensure rapid oil circulation and engine wear protection at cold start-up
- Keep-clean technology offers deposit and sludge protection, helping optimise fuel economy
- Designed with an advanced synthetic formulation to offer long, low volatility oil service life

Product highlights

- **Suitable for a wide range of Volkswagen/Audi vehicles**
- **Promotes engine wear protection and performance**
- **Promotes TWC and DPF protection**
- **Helps protect at engine cold start-ups**
- **Offers deposit and sludge resistance**
- **Designed for long, low volatility oil service life**

Selected specification standards include:

ACEA	BMW
Iveco	Mercedes Benz
Porsche	VW

Applications

- Havoline ProDS V SAE 0W-30 is suitable for a large number of Volkswagen/Audi group gasoline and diesel passenger cars and light diesel vans, with or without turbochargers
- Especially designed for extended drain intervals in Europe and is mandatory for VW/Audi diesels with DPFs
- Havoline ProDS V SAE 0W-30 is recommended for vehicles requiring a VW 504.00, VW 507.00 approved engine oil, also known as VW Longlife III oils, and is backwards compatible with other active and obsolete VW/Audi engine oil specifications
- For applications where VW Standard 508.00/509.00 is recommended, Havoline ProDS VB SAE 0W-20 should be used. Havoline ProDS V SAE 0W-30 (VW Standard 504.00/507.00) can be used when allowed by VW as indicated in their car manuals/handbooks
- Havoline ProDS V SAE 0W-30 is unsuitable for some engines. Consult owner manual or handbook if in doubt

Approvals, performance and suitable for use

Approvals

- BMW BMW LL-04
- VW Standard 504.00/507.00
- Porsche C30

Performance

- ACEA C3
- Daimler MB 229.52

Suitable for use

Suitable for use in engines that require:

- VW 502.00/505.01
- VW 503.00 and VW 503.01 (superseded specifications)
- Iveco 18.1811 Class SC1 LV

Typical test data

Test	Test Methods	Results
Viscosity Grade		0W-30
Shelf Life: 60 months from date of filling indicated on the product label		
Density, 15 °C, kg/l	ASTM 4052	0.843
Viscosity, Kinematic at 40 °C, mm ² /s	ASTM D445	61.0
Viscosity, Kinematic at 100 °C, mm ² /s	ASTM D445	12.2
Viscosity Index	ASTM D2270	202
Pour Point, °C	ASTM D97	-48
Flash Point COC, °C	ASTM D92	235

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A Chevron company product