



DELO[®] SYN-TRANS HD ISOCLEAN[®] Certified Lubricant SAE 50

PRODUCT DESCRIPTION

"Delo. Let's go further.[®]"

Delo[®] Syn-Trans HD ISOCLEAN[®] Certified Lubricant is a heavy duty truck manual transmission fluid recommended for service fill of heavy duty manual transmissions, such as those manufactured by **Eaton, Meritor, and Mack**. Chevron ISOCLEAN Certified Lubricants have been certified to meet specified ISO Cleanliness standards at point of delivery using industry leading filtration and testing technology. ISOCLEAN Certified products are the first step for contamination control and maximizing component life.



CUSTOMER BENEFITS

Delo Syn-Trans HD ISOCLEAN Certified Lubricant delivers value through:

- **Ready to use** — Enables users to meet stringent original equipment manufacturers' cleanliness standards for fill lubricants.
- **Flexibility** — ISO Cleanliness targets can be customized to fit your business application needs.
- **Peace of mind** — Each delivery of Chevron ISOCLEAN Certified Lubricant includes an ISOCLEAN Certificate of Analysis.
- **OE fluid cleanliness requirements** — Customized to meet specific equipment manufacturers' fluid cleanliness requirements.
- **Extended drain capabilities** — Proven field performance for on-highway drain intervals of 500,000 miles and greater.
- **Excellent thermal and oxidation stability** — The synthetic hydrocarbon base oil used in this product provides outstanding stability.

- **A high viscosity index and low pour point** — The performance of the synthetic hydrocarbon base stock provides extremely broad operating temperature ranges when compared with conventional mineral oil based lubricants.
- **Protection against gear wear and copper corrosion** — The unique additive package can protect gears without using the "active sulfur" agents commonly found in automotive axle oils. This results in little to no corrosion and long life for copper-containing parts, such as oil coolers, bushings, and thrust washers.

FEATURES

Delo Syn-Trans HD ISOCLEAN Certified Lubricant is a heavy duty truck manual transmission fluid.



It is manufactured from synthesized hydrocarbon base fluids which have excellent thermal and oxidation stability, a high natural viscosity index, and a low pour point.

Delo Syn-Trans HD ISOCLEAN Certified Lubricant's outstanding low temperature flow properties and natural high viscosity index provides exceptional all-weather, year-round performance in heavy duty truck transmissions. Its use permits easy shifting in extremely cold weather and minimal drag and gear wear during startup.

Product(s) manufactured in the USA and Colombia.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

1 July 2021
TTF-27 ISOCLEAN

© 2014-2021 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Delo, Delo. Let's go further., ISOCLEAN, ISOSYN and the ISOSYN logo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

APPLICATIONS

Delo Syn-Trans HD ISOCLEAN Certified Lubricant is recommended for service fill of heavy duty manual transmissions, such as those manufactured by **Eaton**, **Meritor**, and **Mack**.

This product is not recommended for use as an engine crankcase oil.

Delo Syn-Trans HD ISOCLEAN Certified Lubricant

- meets the performance requirements of:
 - **API Service Category** MT-1
 - **Meritor** O-81

Consult with your Chevron Lubricant Representative or Chevron ISOCLEAN Certified Lubricants Marketer to set specific ISO Cleanliness targets for your business application.

TYPICAL TEST DATA

SAE Grade	50
<i>Product Number</i>	223091
<i>SDS Number</i> U.S. Colombia	35590 41477
API Gravity	32.5
Viscosity, Kinematic cSt at 40°C cSt at 100°C	141 18.3
Viscosity Index	144
Flash Point, °C(°F)	136(277)
Pour Point, °C(°F)	-42(-44)
FZG Scuff Test, Passing Load Stage	12
ASTM D1500 Color	1.5 (light pale)

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.