



CALTEX

# Havoline® ProDS Fully Synthetic ECO SAE 0W-20

Product Data Sheet



## Customer benefits

Havoline ProDS Fully Synthetic ECO SAE 0W-20 with Deposit Shield Technology uses the latest fully synthetic base oils and advanced additives technologies including special antioxidants and friction modifiers to provide outstanding protection and performance. It exhibits outstanding protection against heat, pressure, corrosion, and wear while providing excellent oxidation protection and volatility control, and superior cold temperature performance over partial synthetic and mineral motor oils. It meets or exceeds the requirements of API SP Resource Conserving and ILSAC GF-6 and most demanding automaker standards.

Havoline ProDS Fully Synthetic ECO SAE 0W-20 is formulated to:

- Provide advanced protection against sludge, varnish and deposit buildup to keep modern engines running cleaner, stronger, and for longer
- Help maximize the power of your engine while maintaining fuel efficiency and cleanliness.
- Provide outstanding protection against wear and corrosion to help preserve engines and turbocharger durability
- Provide outstanding mitigation against Low Speed Pre-Ignition (LSPI) in turbocharged gasoline direct injection (GDI) engines to protect critical engine parts
- Exceptional turbocharger cleanliness protection
- Reduced evaporative oil loss at high temperature compared to conventional and part synthetic motor oils
- Excellent degradation control for long automaker-recommended oil change intervals

**SAE 0W-20** is licensed under the dexos1 Gen 3 specification (License no. D335BBCI089). It is recommended for use in FCA, Ford, GM, Honda, Mazda, Mitsubishi, Nissan and Toyota engines for either SAE 0W-20 or SAE 5W-20 applications. It can increase engine efficiency and improve fuel economy and provides excellent engine protection in applications recommending SAE 0W-20 or 5W-20 motor oils.

## Product features

**Havoline ProDS Fully Synthetic ECO SAE 0W-20** is premium fully synthetic motor oil with Deposit Shield Technology, a proprietary cleaning booster, designed to provide advanced protection that prolongs the peak performance and efficiency of high performance engines, particularly under harsh stop-and-go driving conditions, extreme temperatures and heavy loads. It provides outstanding protection for vehicles with direct-injection and turbochargers and those that require a full synthetic motor oil.

A Chevron company product



*continued*

## Applications

Havoline ProDS Fully Synthetic ECO SAE 0W-20 with Deposit Shield technology is recommended for use in:

- Advanced, high power density and performance engines with turbochargers, gasoline direct injection,
- Vehicles operating in extreme hot or cold or stop-and-go driving conditions
- Passenger cars, pickup trucks, SUVs and working vans in new and older vehicles
- FCA, Ford, GM, Honda, Mazda, Nissan and Toyota engines for either SAE 0W-20 or SAE 5W-20 applications
- Hybrid and gasoline vehicles where an API SP or ILSAC GF-6A SAE 0W-20 lubricant is recommended

## Performance and specifications

Havoline ProDS Fully Synthetic ECO SAE 0W-20 is licensed under the dexos1 Gen 3 specification (License no. D335BBCI089), and meets or exceeds the following OEM specifications and industry standards:

- API SP/ Resource Conserving    Licensed
- ILSAC GF-6A                            Licensed
- GM dexos1 Gen 3                    Licensed
- Ford WSS-M2C962-A1<sup>1</sup>            Meets
- GM 6094M                                Meets

<sup>1</sup>Compatible with Ford WSS-M2C947-A1/B1



continued

## Typical test data

HAVOLINE® ProDS FS ECO	TEST METHOD	RESULTS
<b>SAE Grade</b>		<b>0W-20</b>
<b>Product Code</b>		<b>500292</b>
<b>Density at 15°C kg/l</b>	ASTM D4052	0.844
<b>Kinematic viscosity</b>		
mm <sup>2</sup> /s @ 40°C	ASTM D445	44.3
mm <sup>2</sup> /s @ 100°C	ASTM D445	8.4
<b>Viscosity Index</b>	ASTM D2270	169
<b>Pour Point, °C</b>	ASTM D5950	-45
<b>Flash Point, °C</b>	ASTM D92	233
<b>Phosphorus mass %</b>	ASTM D4951	0.077
<b>Ash, sulphated mass %</b>	ASTM D874	0.9
<b>Zinc, mass %</b>	ASTM D4951	0.089

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Global Lubricants: Africa, Middle East and Pakistan

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit [www.caltexoils.com](http://www.caltexoils.com).

**For more information, go to [www.chevronlubricants.com](http://www.chevronlubricants.com)**

A Chevron company product  
All trademarks are property owned by Chevron Intellectual Property LLC.

HAVOLINE-PRO-DS-FS-ECO-SAE-0W20/MEA/PDSv3\_17/01/2024  
© 2024 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.