



# Delo® Syn-THF XC

High performance synthetic wet brake transaxle fluid  
(Supersedes Textran WBT)

Product Data Sheet



## Customer benefits

- Offers good extended drain intervals compared to conventional wet brake transaxle fluids
- High performance shear stable additive system promotes increased gear protection with viscosity retention throughout fluid lifetime
- Formulated for low temperature fluidity, providing faster cold starts and optimised viscosity, offering improved fuel economy
- High Viscosity Index, promoting sufficient oil viscosity retention for effective lubrication even at high operating temperatures
- Good oxidation stability, helping resist the formation of harmful sludge, lacquer or deposits

## Applications

- Delo Syn-THF XC is designed for use in the axles of off-road and construction machines that are equipped with built-in wet brakes. The amount of EP additive used in the formulation of Delo Syn-THF XC is higher than is typically used in products of this type, providing increased gear protection
- The oxidation stability of the synthetic base oils in the formulation means that compared to conventional fluids, Delo Syn-THF XC offers significantly longer service intervals; and its temperature resistance means that it may be used in more arduous operating conditions
- The low temperature characteristics of Delo Syn-THF XC offer a significant reduction in the warm-up period before the machine is ready to operate
- Delo Syn-THF XC has a lower kinematic viscosity than is typical for fluids used in this type of application - it has been optimised to help improve machine efficiency while still providing protection to machine components. The high Viscosity Index means that the fluid has a wide operating temperature window. It is achieved by a formulating the product with synthetic base oils with a naturally high VI, plus a highly shear stable Viscosity Index Improver. This combination promotes the maintenance of the viscosity and VI at a consistent level through the fluid's service lifetime

## Product features:

- Delo Syn-THF XC is a high performance synthetic wet brake transaxle fluid designed for applications where a Volvo WB 102 fluid is required. Delo Syn-THF XC is formulated with a high performance synthetic base fluid, in combination with a specially optimised additive system.

A Chevron company product



continued

## Approvals, performance and recommendations

### Approvals

- Volvo Transmission oil 97304 (WB 102)

### Recommendations

- API GL-4 <sup>[1]</sup>

<sup>[1]</sup> Under low speed-high torque conditions. Not recommended for on-highway application

### Typical test data

DELO® SYN-THF XC	TEST METHOD	RESULTS
<b>Shelf Life: 60 months from date of filling indicated on the product label</b>		
<b>Product Code</b>		510127
<b>Kinematic viscosity,</b> mm <sup>2</sup> /s @ 40°C	ASTM D445	41
mm <sup>2</sup> /s @ 100°C	ASTM D445	7.8
<b>Viscosity, Brookfield,</b> -40°C, mPa.s	ASTM D2983	30,000
<b>Viscosity Index</b>	ASTM D2270	166
<b>Density, 15°C, kg/l</b>	ASTM D1298	0.851
<b>Flash Point COC, °C</b>	ASTM D92	240
<b>Pour Point, °C</b>	ASTM D5950	-45

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Global Lubricants: Africa, Middle East and Pakistan

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit [www.caltexoils.com](http://www.caltexoils.com).

**For more information, go to [www.chevronlubricants.com](http://www.chevronlubricants.com)**

A Chevron company product  
All trademarks are property owned by Chevron Intellectual Property LLC.

DELO-SYN-THF-XC/MEA/PDSv1\_07/09/2022  
© 2022 Chevron Lubricants; Africa, Middle East and Pakistan. All Rights Reserved.