



Delo Gold Ultra N SAE 15W-40

Heavy duty diesel engine oil

Product description

Delo® Gold Ultra N SAE 15W-40 is a heavy duty diesel engine oil, designed for use in engines requiring API CI-4 or lower performance lubricants.

Delo Gold Ultra N SAE 15W-40 engine oil is formulated with high quality additives to promote good, durable service and engine performance throughout longer drain intervals*.

Customer benefits

- Formulated to reduce low temperature sludge and high temperature oxidation and piston deposit formation, offering optimum efficiency
- Detergency performance and acid control help resist bearing corrosion, bore polishing and wear
- Designed for soot related wear and deposit protection, and helps prevent excessive viscosity increase and filter plugging

Product highlights

- **Formulated for low and high temperature sludge and oxidation protection**
- **Offers acid control, corrosion, bore polishing and wear resistance**
- **Designed for soot, deposit and viscosity increase protection**

Selected specification standards include:

API

Applications

- Formulated for use in naturally aspirated and turbocharged diesel engine operations with or without intercooling in trucks, busses, light commercial vehicles, off-road vehicles, construction equipment, agricultural vehicles and marine diesel engines.
- Designed to provide good performance in most exhaust gas recirculation (EGR) engines, in most engines fitted with selective catalytic reduction (SCR) and engines without diesel particulate filter (DPF) after treatment systems.

Approvals, performance and recommendations

Performance

- API CI-4
- * Recommendations may differ between engine manufacturers so Drivers Manuals and/or Dealers shall be consulted if in doubt.

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 15W-40
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.886
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	14.5
Pour point, °C	ASTM D97	-42
Flash point COC, °C	ASTM D92	234
Sulphated Ash, %wt	ASTM D874	1.5

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A **Chevron** company product