



Texaco Heavy Duty N SAE 30 & 40

Heavy-duty diesel engine oil

Product description

Texaco Heavy Duty N SAE 30 and 40 are proven performance heavy-duty diesel engine oils designed for use in a wide range of older passenger car and light duty commercial vehicle equipped with gasoline or diesel engines where API SJ, API CF or lower performance engine oils are required.

Customer benefits

- Formulated for protection against engine wear and bore polishing, helping increase engine output and reduce maintenance downtime
- Designed to help reduce low temperature sludge build-up, offering improved engine protection and performance in cold environments
- Offers protection against high temperature oxidation and piston deposit formation, helping reduce maintenance downtime and costs
- Detergency performance and acid control help maintain reliability, contributing to engine and bearing corrosion prevention, and efficient uptime.

Product highlights

- **Formulated for engine wear and bore polishing resistance**
- **Designed to reduce low temperature sludge**
- **Offers high temperature oxidation protection**
- **Promotes acid control and corrosion prevention**

Selected specification standards include:

API

Applications

- Texaco Heavy Duty N SAE 30 & 40 can be used in following applications that require API SJ and/or API CF performance. Product is not suitable for applications requiring higher level of API performance.
- Gasoline and diesel engines (high-speed, four-stroke)
- Commercial road transport
- Off-highway vehicles
- Agricultural tractors
- High speed diesel engines in marine service
- Generator sets
- Mobile hydraulic systems (where oil type and viscosity are appropriate)

Not recommended for use in gasoline engines that require API SL or higher performance or ACEA-classified oils, in any gas-fueled (CNG or LPG) engines, in any diesel engine requiring better performance as API CF, or in any motorcycle engines.

API SJ performance oils are intended for use in vehicles manufactured before 2001. For vehicles manufactured after 2001, the car manual should be checked.

Approvals, performance and recommendations

Performance

- API SJ/CF

| Typical test data | | | |
|--|--------------|---------|--------|
| Test | Test Methods | Results | |
| Viscosity Grade | | SAE 30 | SAE 40 |
| Shelf Life: 60 months from date of filling indicated on the product label | | | |
| Density at 15°C, kg/l | ASTM D4052 | 0.89 | 0.90 |
| Kinematic viscosity at 100°C, mm ² /s | ASTM D445 | 11.0 | 14.5 |
| Pour point, °C | ASTM D97 | -27 | -27 |
| Flash point COC, °C | ASTM D92 | 250 | 270 |

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A **Chevron** company product