



Texaco Motor Oil N SAE 40

Gasoline and diesel engine oil

Product description

Texaco Motor Oil N SAE 40 is a gasoline and diesel engine oil formulated for use in passenger car and light truck engines where API SF and/or API CD performance is required.

Customer benefits

- Anti-wear additive system formulated to offer good protection for critical components, helping extend gasoline and diesel engine life and long-term reliability
- Designed to protect against engine rust and corrosion, helping ensure vehicle protection, reliability and performance
- Powerful detergent and dispersant systems help maintain piston and ring cleanliness, engine reliability and power

Product highlights

- **Helps extend engine life and long-term reliability**
- **Formulated for rust and corrosion protection**
- **Designed for engine reliability and power**

Selected specification standards include:

API

Applications

Texaco Motor Oil N SAE 40 can be used in following applications that require API SF and/or CD performance. Product is not suitable for applications requiring higher level of API performance.

- Mixed fleets of diesel engines (high-speed, four-stroke)
- Gasoline engines (four-stroke) in mixed fleets of both diesel and gasoline engines
- Commercial road transport
- Off-highway vehicles
- Agricultural tractors
- High speed diesel engines in marine service (e.g., fishing boats, river transport)
- Generator sets

Approvals, performance and recommendations

Performance

- API SF/CD

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 40
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.895
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	14.5
Pour point, °C	ASTM D97	-24
Flash point COC, °C	ASTM D92	273
Sulphated Ash, %wt	ASTM D874	-

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A **Chevron** company product