



Havoline® ProDS PR SAE 5W-30

Premium performance synthetic engine oil

Product description

Havoline ProDS PR SAE 5W-30 is a premium performance synthetic engine oil specifically formulated with advanced additive technologies to meet demanding PSA B71-2290 engine lubrication requirements.

Havoline ProDS PR SAE 5W-30 is suitable for use in gasoline and diesel passenger cars, and light duty commercial diesel engines. It is a mid SAPS oil formulation, compatible with diesel particulate filters (DPF), gasoline particulate filters (GPF) and three-way catalysts (TWC).

Customer benefits

- Designed for advanced engine and emission system protection, helping reduce maintenance time and cost over extended drain intervals
- Mid SAPS technology offers protection to emissions control catalysts and particulate filters, helping minimise exhaust emissions
- Formulated with advanced cleaning additives to help minimise deposits and harmful sludge build-up, offering extended engine life
- Reliable oxidation stability promotes engine fuel efficiency performance over lubricant service lifetime
- Synthetic base oil technologies offer low oil volatility with oxidation stability, reducing oil consumption and improving oil service life
- PSA tests prove Havoline ProDS PR SAE 5W-30 does not contribute to engine super knock and potential severe engine damage caused by Low Speed Pre-Ignition (LSPI)

Product highlights

- **Designed for engine and emission system protection**
- **Offers protection to catalysts and particulate filters**
- **Helps minimise deposits and sludge**
- **Promotes engine fuel efficiency performance**
- **Offers reduced oil consumption**
- **PSA tests prove no contribution to LSPI**

Selected performance standards include:

ACEA	Iveco
PSA	

Applications

- Havoline ProDS PR SAE 5W-30 is suitable for use in gasoline and diesel passenger cars and light diesel vans from Euro 5 onwards - with or without turbochargers.
- Havoline ProDS PR SAE 5W-30 is intended for use in cars equipped with a particulate filter (GPF or DPF).

Consult owner manual or handbook if in doubt.

Approvals, performance and suitable for use

Performance

- ACEA C2
- PSA B71-2290

Suitable for use

Havoline ProDS PR SAE 5W-30 is suitable for use in engines requiring:

- Iveco 18.1811 Class SC1

Typical test data		
Test	Test Methods	Results
Viscosity Grade		5W-30
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.85
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	56.5
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	9.8
Viscosity Index	ASTM D2270	161
Pour Point, °C	ASTM D97	-39
Flash Point COC, °C	ASTM D92	224

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A Chevron company product