

Rando[®] HD

Premium Anti-Wear Hydraulic Oil



Product description

Rando HD[®] oils are formulated with premium base oils and robust additives to help protect hydraulic pumps and systems. Rando HD oils help ensure good film strength between metal surfaces and is further enhanced by antiwear additive protection.

Rando HD oils help to deliver long oil service life with its premium base oil quality used in formulation.

Customer benefits and product features

Customer benefits

- **Protects equipment**
Robust anti-wear additive package helps minimize wear by protecting surfaces when loads cause breakdown of the lubricant film.
- **Minimizes downtime**
Rust and oxidation inhibitors help to prevent the production of abrasive particles from rust formation, and deposits, varnishes and sludges from oil breakdown, which can damage equipment surfaces and seals, and block filters prematurely.
- **Smooth operation**
Good hydrolytic stability and water separation characteristics promote excellent filterability in the presence of water contamination. Good anti-foam and air release properties help ensure smooth operation and system efficiency.
- **Longer oil service life**
The use of premium base stocks helps resist oil thickening and deposit formation in service to minimize the possibility of an unscheduled change of hydraulic fluid. Oxidation test life is higher than solvent extracted hydraulic oil products.

Product features

- Robust anti-wear additive protects equipment.
- Rust and oxidation inhibitors help to prevent deposits and minimize downtime.
- Good hydrolytic stability and water separation help with smooth operation.
- Premium Group II base oil helps to ensure longer oil life.

Rando[®] HD

Premium Anti-Wear Hydraulic Oil



Applications

General hydraulics in both mobile or stationary equipment using gear, vane or piston pumps across a wide range of industries.

- Industrial hydraulic systems
- Hydraulics of mobile and construction equipment where a water separating oil is required
- Hydraulic systems with vane, gear or piston pumps
- Plastic injection molding machines
- Machine tools
- Enclosed gear systems (dependent on load)
- Industrial circulating systems

Approvals, performance and recommendations

Rando HD are approved against:

- Parker Hannifin (Denison Hydraulics) HF-0 (ISO 32, 46, 68)
- Eaton Vickers I-286-S [industrial applications], M2950-S [mobile applications] (ISO 32, 46, 68)
- David Brown Industrial Gears 0A (ISO 32), 1A (ISO 46), 2A (ISO 68), 3A (ISO 100), 4A (ISO 150), 5A (ISO 220)

Rando HD oils meet the requirements of various industry standards:

- Bosch Rexroth former specification RE 90220 (ISO 32, 46, 68)
- DIN 51502:1990, HLP fluid (ISO 32, 46, 68, 100)
- DIN 51524:2006-04 Part 2, HLP (ISO 32, 46, 68, 100)
- Cincinnati Machine P-68 (ISO 32), P-69 (ISO 68) and P-70 (ISO 46)
- ISO 6743:1999 Part 4, HM fluid
- ISO 11158:2009, HM
- SAE MS1004 HM (ISO 32, 46, 68, 100)
- US Steel 126 and 127 (ISO 32, 46, 68)

Rando[®] HD

Premium Anti-Wear Hydraulic Oil



Typical test data

RANDO [®] HD							
ISO Viscosity Grade	32	46	68	100	150	220	320
Product Code	520210	520211	520212	520213	520214	520215	520220
Viscosity, Kinematic							
mm ² /s at 40°C	30.5	44	65	95.5	143	220	304
mm ² /s at 100°C	5.4	6.8	8.9	10.8	14.3	19.0	23.4
Viscosity Index	110	110	110	97	97	97	96
Flash Point, °C	216	238	240	240	250	274	277
Pour Point, °C	-33	-33	-30	-21	-15	-12	-12
FZG Fail Load Stage	12	12	12	12	12	12	12
Air Release at 50°C, min	1.1	2	3.5	12	15	-	-
Oxidation Stability (TOST)	>5000	>4500	>4500	>2000	>1500	>1000	>1000

2205

Minor variations in product typical test data are to be expected in normal manufacturing.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

Visit [Product Information Center](#) >

Rando HD/Asia Pacific/CHV/PDSv1_04/2024



A Chevron company product

© 2024 Chevron Products Company. Asia-Pacific.
All Rights Reserved.