



Ursa[®] Premium FE SAE 5W-30

High performance synthetic heavy-duty engine oil

Product description

Ursa Premium FE SAE 5W-30 is a high performance synthetic heavy-duty engine oil. It is designed to offer fuel saving performance across a range of modern heavy-duty diesel engines over extended drain intervals.

Ursa Premium FE SAE 5W-30 is formulated to conform to ACEA and original equipment manufacturers performance standards for modern heavy-duty diesel engines.

Customer benefits

- Designed to deliver good fuel economy performance while maintaining robust and reliable engine wear protection
- Low viscosity synthetic base oils offer cold start-up protection in diesel engines in sub-zero temperatures
- Helps keep piston rings clean and offers protection against harmful valve and piston land deposit formation
- Formulated for soot dispersancy and wear control, helping offer optimum service life with minimal maintenance
- Reduces inventories and suitable for a wide range of applications, including older engines

Applications

- Ursa Premium FE SAE 5W-30 is recommended for use in heavy duty truck and bus operations, especially where extended drains are required. The oil is backwards compatible for older engines. For the correct oil drain intervals, the relevant engine manual or the manufacturer must be consulted
- Ursa Premium FE SAE 5W-30 is recommended for use in other commercial and off-highway engines where manufacturers do not specifically approve oils, but do publish performance requirements for service applications, such as Iveco (standard 18-1804-TFE)

Product highlights

- **Designed to deliver fuel economy performance**
- **Offers sub-zero cold start-up protection**
- **Promotes valve and piston deposit resistance**
- **Formulated for soot dispersancy and wear control**
- **Helps reduce inventories and costs**

Selected specification standards include:

ACEA	DAF
Daimler	Deutz
Iveco	Mack
MAN	Mercedes-Benz
MTU	Renault
Voith	Volvo

Approvals, performance and suitable for use

Approvals

• Daimler Trucks	DTFR 15B120 (previously MB 228.5)
• Deutz	DQC IV-18
• Mack	EO-N
• MAN	M3277
• Mercedes Benz	MB 235.28
• MTU	Oil Category 3
• Renault	RLD-2
• Volvo	VDS-3
• Voith	Retarder B

Performance

• ACEA	E4, E7
• DAF	Extended Drain (Euro 0-III engines)
• Iveco	18-1804-TFE
• Renault	RLD

Suitable for use

Suitable for use in applications requiring:

- Renault RD and RD-2
- Volvo VDS-2

Typical test data		
Test	Test Methods	Results
Viscosity Grade		SAE 5W-30
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.862
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	71.4
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	12.1
Viscosity Index	ASTM D2270	166
Pour point, °C	ASTM D5950	-51
Flash point COC, °C	ASTM D92	230
Total Base Number, mg KOH/g	ASTM D2896	15.1
Sulphated Ash, %wt	ASTM D874	1.7

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

A **Chevron** company product