



Havoline ProDS FV SAE 0W-20

Premium performance synthetic engine oil

Product description

Havoline® ProDS FV SAE 0W-20 is a premium performance synthetic passenger car engine oil specifically designed for use in Volvo passenger car VEA (Volvo Engine Architecture) Drive-E power trains requiring Volvo RBS0-2AE engine oil.

Havoline ProDS FV SAE 0W-20 is a premium mid-SAPS oil, formulated with quality synthetic base oils in combination with an advanced additive system designed to help deliver long-life engine wear resistance, cold temperature protection, reduced exhaust emissions, and improved fuel efficiency performance.

Customer benefits

- Designed to reduce engine friction and provide improved fuel economy without compromising on engine reliability and durability
- Low temperature fluidity aids rapid lubricant circulation during cold engine starts, contributing to increased engine protection
- Synthetic base oils in combination with advanced cleaning additives minimise deposit formation and wear, helping extend engine life
- Advanced cleaning additives designed to minimise deposit and sludge build-up, help extend engine life and maintain fuel economy

Product highlights

- **Designed for Volvo Drive-E power trains**
- **Formulated to help improve fuel economy**
- **Advanced anti-wear formulation for good wear protection**
- **Low temperature engine protection**
- **Keep-clean additive package to help minimise deposit and sludge build-up**

Selected specification standards include:

ACEA	API
Volvo	

Applications

- Havoline ProDS FV SAE 0W-20 is suitable for gasoline, diesel & hybrid passenger cars or light diesel vans - with or without turbocharger°.
- Havoline ProDS FV SAE 0W-20 is designed for the Volvo passenger car VEA (Volvo Engine Architecture) Drive-E Power train generation requiring Volvo RBS0-2AE engine oil.

°Havoline ProDS FV SAE 0W-20 is unsuitable for some engines. Consult owner manual or handbook if in doubt.

Approvals, performance and suitable for use

Approvals

- Volvo RBS0-2AE

Performance

- ACEA C5
- API SP

Typical test data

Test	Test Methods	Results
Viscosity Grade		SAE 0W-20
Shelf Life: 60 months from date of filling indicated on the product label		
Density at 15°C, kg/l	ASTM D4052	0.843
Kinematic viscosity at 40°C, mm ² /s	ASTM D445	42.0
Kinematic viscosity at 100°C, mm ² /s	ASTM D445	8.7
Viscosity Index	ASTM D2270	194
Pour Point, °C	ASTM D97	-42
Flash Point COC, °C	ASTM D92	234

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see www.texacolubricants.com.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A Chevron company product