

# Delo<sup>®</sup> Gold NG

## Heavy Duty Mobile Gas Engine Oil



### Product description

Delo<sup>®</sup> Gold NG with ISOSYN<sup>®</sup> Technology is a proven CNG/LNG oil formulated to deliver protection in a wide variety of medium and heavy duty CNG-fuelled applications.

### Customer benefits and product features

#### Customer benefits

- **Alternative fuel performance** - Formulated especially for medium and heavy-duty vehicles powered by CNG-fuelled engines.
- **Clean crankcases and top decks** - Minimize the formation of sludge in the crankcase and in the valve rocker cover/top deck area.
- **Prevents corrosion** - Good oxidation and nitration resistance help prevent bearing corrosion.
- **Better piston and ring belt deposit control** - Optimised and proven low ash additive system which provide good deposit control throughout the entire engine.

### Applications

- Suitable for use in various CNG model engines for standard drain mobile applications

# Delo<sup>®</sup> Gold NG

Heavy Duty Mobile Gas Engine Oil



## Typical test data

| DELO <sup>®</sup> GOLD NG                          | RESULTS       |               |
|----------------------------------------------------|---------------|---------------|
| <b>SAE Grade</b>                                   | <b>15W-40</b> | <b>20W-50</b> |
| <b>Product Code</b>                                | <b>500646</b> | <b>500647</b> |
| Base No.,<br>D2896, mg KOH/g                       | 5.41          | 5.4           |
| Sulfated Ash, mass %                               | 0.58          | 0.58          |
| Phosphorus, mass %                                 | 0.07          | 0.07          |
| Flash Point, °C                                    | 240           | 266           |
| Pour Point, °C                                     | -33           | -33           |
| Viscosity, Kinematic,<br>mm <sup>2</sup> /s @ 40°C | 116           | 170           |
| mm <sup>2</sup> /s @ 100°C                         | 15.1          | 19.1          |
| Viscosity Index                                    | 136           | 127           |
| Zinc, mass %                                       | 0.08          | 0.08          |

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the [Product Information Center](#).

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center.

[Visit Product Information Center >](#)

Delo<sup>®</sup> Gold NG/Asia Pacific/CHV/PDSv1\_03/2024



**A Chevron company product**

© 2024 Chevron Products Company. Asia Pacific.  
All Rights Reserved.