# Black Pearl SRI 2 (Formerly SRI Grease)



## **High Temperature Anti-friction Bearing Polyurea Grease**

#### Product description

**Black Pearl SRI 2** is a specially formulated grease containing a highly refined paraffinic base oil, synthetic polyurea ashless organic thickener and high performance rust and oxidation inhibitors, for the lubrication of anti-friction ball, needle and roller bearings operating at speeds up to and above 10,000 rpm, operating at higher temperatures, or where water or salt water may penetrate bearings.

### Customer benefits and product features

#### **Customer benefits**

- Long service life at high temperatures
- Synthetic polyurea thickener is oxidatively stable at elevated temperatures. This, coupled with its high dropping
  point and the highly refined base oil and high performance anti-oxidant components, enables operation for periods
  at high temperatures.
- Long bearing life under severe conditions
- Special rust and corrosion inhibitors provide protection to metal surfaces in wet conditions, even in a salt water environment. Passes Bearing Rust Test, ASTM D5969 with synthetic sea water. Outstanding oxidation stability helps prevent the formation of corrosive oxidation by-products.
- Excellent resistance to water washout
- Synthetic polyurea thickener has excellent inherent water resistance.
- Wide application range
- Wide temperature range capability and excellent water resistance allow use in a wide variety of operating conditions.

# Black Pearl SRI 2 (Formerly SRI Grease)



## **High Temperature Anti-friction Bearing Polyurea Grease**

### **Applications**

Black Pearl SRI 2 may be used in:

- High speed bearings operating under high or low temperature conditions
- Unsealed bearings where there is the likelihood of fresh or salt water getting into the bearings
- Sealed-for-life bearings
- Industrial ball and roller bearings
- · Electric motor, fan, and air-conditioning unit bearings
- Automotive alternator, generator and starter motor bearings
- Water pump bearings
- Boat trailer wheel bearings

Usable temperature range in continuous service from -30 to 150°C. Maximum temperature for short term exposure is 175°C.

### Product approvals, performance and recommendations

#### Performance standards

Suitable for use in high-speed bearings from major bearing OEMs including SKF, FAG-Schaeffler, NSK. Consult the OEM representatives for independent verification, updates and recommendations.

# Black Pearl SRI 2 (Formerly SRI Grease)



## **High Temperature Anti-friction Bearing Polyurea Grease**

### Typical test data

BLACK PEARL SRI 2	TEST METHOD	RESULTS
Product Code		540940
Operating Temperature, °C		
Minimum		-30
Maximum		150
ISO Viscosity Grade Base Oil Equivalent		100
Base Oil Viscosity, Kinematic cSt @ 40°C cSt @ 100°C	ASTM D445 ASTM D445	110.9 11.96
Thickener Type		Synthetic Polyurea
Penetration, at 25°C Worked (60 strokes)	ASTM D217	282
Dropping Point, °C	ASTM D2265	255
Corrosion Preventive Properties	ASTM D5969	Pass
Thickener (Polyurea), m%		6.3
Color		Dark Green

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended. Produced by Chevron Global Lubricants: Asia Pacific.

ENVIRONMENT, HEALTH and SAFETY. Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit the <u>Product Information Center</u>.

This Product Data Sheet (PDS) was produced for the Asia Pacific region based on the best available information at the time of issue. The specific information included may not directly reflect the market or conditions, and may vary. For the most up-to-date, country-specific information, please contact your local customer service center