



# Havoline ProDS P 0W-20

## Premium performance synthetic engine oil

### Product description

Texaco Havoline® ProDS P SAE 0W-20 is a premium performance synthetic engine oil specifically formulated with advanced technology additives to be suitable for use in vehicles with PSA B71-2010 engine lubrication requirements.

Havoline ProDS P SAE 0W-20 is suitable for use in gasoline and diesel passenger cars, and light duty diesel vans. It is a mid SAPS oil compatible with diesel particulate filters (DPF), gasoline particulate filters (GPF) and three-way catalysts (TWC).

### Customer benefits

- Designed to maximise vehicle uptime throughout extended drain intervals through advanced engine and emission system protection.
- Mid SAPS formulation offers optimum protection to diesel particulate filters and catalysts.
- Formulated for low temperature fluidity and rapid engine oil circulation at cold starts, promoting engine protection and fuel efficiency.
- Advanced cleaning additives help minimise deposit and sludge build-up, offering extended engine life and fuel economy.
- Synthetic base oil and additive combination offers reduced engine oil volatility, oil consumption, oxidation, with improved thermal stability.
- Aids low speed pre-Ignition (LSPI) protection helping prevent super knock and severe damage in PSA engines.

### Product highlights

- **Designed to contribute to engine and emissions system protection**
- **Mid SAPS helps protect DPF and TWC systems**
- **Promotes cold start protection and fuel efficiency**
- **Helps minimise deposits and sludge**
- **Designed for reduced engine oil volatility**
- **Aids low speed pre-Ignition (LSPI) protection**

#### Selected specification standards include:

ACEA	API
PSA	

## Applications

- Havoline ProDS P SAE 0W-20 is suitable for use in gasoline and diesel passenger cars or light diesel vans from Euro 6 onwards - with or without turbocharger; with or without particulate filters (GPF/DPF) fuelled with European type of fuels and for hybrid vehicles.
- Havoline ProDS P SAE 0W-20 is designed for Euro 6 vehicles requiring PSA B71-2010 engine oils. It applies to recent Peugeot and Citroen engines (DV5R and EB2DT) especially these equipped with Blue HDi, PureTech using stop & start technologies, and hybrid engines.
- Havoline ProDS P SAE 0W-20 is unsuitable for some engines.

Consult owner manual or handbook if in doubt.

## Approvals, performance and suitable for use

### Performance

- ACEA C5
- API SP
- PSA B71-2010

## Typical test data

Test	Test Methods	Results
Viscosity Grade		SAE 0W-20
<b>Shelf Life: 60 months from date of filling indicated on the product label</b>		
Density at 15°C, kg/l	ASTM D4052	0.844
Kinematic viscosity at 40°C, mm <sup>2</sup> /s	ASTM D445	41
Kinematic viscosity at 100°C, mm <sup>2</sup> /s	ASTM D445	8.1
Viscosity Index	ASTM D2270	176
Pour Point, °C	ASTM D97	-45
Flash Point COC, °C	ASTM D92	230

The typical test data set out above does not constitute a specification. It is indicative only and can be affected by allowable production tolerances. Chevron may modify this test data. Modified data will supersede all previous data, so please ensure you refer to the latest version of this Product Data Sheet (PDS).

**Disclaimer: Data provided in this Product Data Sheet (PDS) is based on standard tests under laboratory conditions and is indicative only. This product should not be used for any purpose other than those expressly set out in this PDS. The user has sole responsibility for verifying that this product is suitable for the user's intended application. Neither Chevron nor its subsidiaries (i) make any warranty or representation as to the accuracy or completeness of this PDS; and/or (ii) accept liability for any loss or damage suffered as a result of the use of this product other than in accordance with the terms of this PDS.**

When disposing of used product, take care to protect the environment and follow local legislation.

Safety Data Sheets (SDS's) are available for all Chevron products. If you require a SDS or any further information regarding a Chevron product, please contact your local sales office or see [www.texacolubricants.com](http://www.texacolubricants.com).

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A Chevron company product